



White
100005920 - 2"x18" Field Tile - Gloss




Light Grey
100005921 - 2"x18" Field Tile - Gloss



Beige
100005922 - 2"x18" Field Tile - Gloss




Aquamarine
100005923 - 2"x18" Field Tile - Gloss



Green
100005924 - 2"x18" Field Tile - Gloss



Sky
100005925 - 2"x18" Field Tile - Gloss



Blue
100005926 - 2"x18" Field Tile - Gloss



Red
100005927 - 2"x18" Field Tile - Gloss



Chroma
Glazed Porcelain


Photo Features 2"x18" Field Tile - Gloss in Aquamarine.

SIZING & PACKAGING

Type	Aquamarine Item Code	Beige Item Code	Blue Item Code	Green Item Code	Light Grey Item Code	Red Item Code	Sky Item Code	White Item Code	Size	Description	Pcs / Ctn	Sf / Ctn
Field	100005923	100005922	100005926	100005924	100005921	100005927	100005925	100005920	2"x18"	Field Tile - Gloss	32	7.42

ANSI TECHNICAL SPECIFICATIONS

	DCOF Acutest	PEI Rating ASTM# C1027	Frost Resistant ASTM# C1026	Scratch Resistance MOHS	Breaking Strength ASTM# C648	Water Absorption ASTM# C373	Chemical Resistance ASTM# C650
Results	N/A	4	Unaffected	5	Pass (1,300 ISO)	≤ 0.5%	Unaffected



APPLICATIONS

	Floors	Walls	Countertops	Shower Floors	Shower Walls	Pools/Spas
Residential	●	◐	◐		◐	◐
Commercial		◐	◐		◐	◐



LEGEND

- ◐ Product rated for Interior & Exterior use
- Product rated for Interior use only
- † May be suitable for Exterior Floors
- ∅ Applications & ANSI Technical Specifications do not apply
- * Special Order only

This product is artisanal and may possess inherent size and color variation.

For installation of all polished, polished glazed, lappato, and honed porcelain/ceramic tiles, use a grout release prior to grouting to prevent absorption of the grout into the tile's micropores. Use a grout color that matches the predominant color of the tile. Refer to grout manufacturer's specifications to ensure use of proper grout. Refer to tile manufacturer's specifications to determine if the polished or honed tile is appropriate for commercial applications. Tiles with a polished finish are not appropriate for wet or exterior floor applications. Do not use acidic cleaners.

Merchandising materials and samples are for general reference only and representative of a product's potential characteristics. Tile is subject to variation in color/shade, size, texture, and finish. Field, mosaic and trim tile may not match exactly. Blend tiles from different boxes to achieve consistent shade distribution. Installer and end user must conduct a dry mock layout under proper lighting conditions to inspect the product. Installation constitutes acceptance of the product. Reference the TCNA, ANSI, Manufacturer's specifications, and Bedrosians Care & Maintenance Guide. Improper installation, application, use, care and maintenance voids warranty. We reserve the right to make product changes without notice. Please visit bedrosians.com for current product information.

