



Crema
100006807
9"x60" Stone Polymer Composite Vinyl



Sand
100006809
9"x60" Stone Polymer Composite Vinyl



Khaki
100006810
9"x60" Stone Polymer Composite Vinyl



Linen
100006811
9"x60" Stone Polymer Composite Vinyl



Canvas
100006812
9"x60" Stone Polymer Composite Vinyl



Honey
100006814
9"x60" Stone Polymer Composite Vinyl



Oak
100006813
9"x60" Stone Polymer Composite Vinyl



Driftwood
100006815
9"x60" Stone Polymer Composite Vinyl

Shorewood

Luxury Vinyl (Stone Polymer Composite)

Photo Features 9"x60" Stone Polymer Composite Vinyl in Linen.

SIZING & PACKAGING

Type	Shape	Item Code	Size	Description	Pcs / Ctn	Sf / Ctn
Plank		100000***	9"x60"	Stone Polymer Composite - 20 Mil Wear Layer with UV Cured Polyurethane & Ceramic Bead Finishes	-	-
Trim		100000***	94.5"x2.73"x0.98"	Luxury Vinyl Flush Stair Nose	-	-
		100000***	94.5"x1.77"x0.33"	Luxury Vinyl Reducer	-	-
		100000***	94.5"x1.77"x0.28"	Luxury Vinyl T-Mold	-	-

TECHNICAL SPECIFICATIONS

Standard	Description	Result
ASTMF-387	Total Thickness	6.0 mm
ASTMF-410	Wear Layer Thickness	0.5 mm (20 mil)
ASTME-648	Critical Radiant Flux	Class I
ASTMF-925	Chemical Resistance	No Change in 24 Hours
ASTMF-970	Static Load Limit	2,000 p.s.i.
ASTMF-1514	Resistance to Heat	Pass
ASTMF-1515	Light Resistance	Pass
ASTMF-1914	Residual Indentation	< 0.003"
ISO 23999	Dimensional Stability	Pass
ASTMF-2421	Width	±0.04mm
ASTMF-2421	Length	±1mm
ASTMF-2055	Squareness	<0.25mm
ASTMD-2047	Slip Resistance	Exceeds 0.52 Dry
ISO 23999	Cupping/Curling	≤ 0.1 mm
ASTME-492	Impact Sound Transmission (IIC)	IIC 64
ASTME-90	Airborne Sound Transmission (STC)	STC 61
ASTME-2179	Impact Sound Transmission (ΔIIC)	ΔIIC 24
Performance	Scratch/Scuff Resistance	Excellent
FloorScore Certified	California 01350	Pass
Warranty	Residential	Lifetime
Warranty	Commercial	10 Years

APPLICATIONS


	Floors	Walls	Countertops	Shower Floors	Shower Walls	Pools/Spas
Residential	●					
Commercial	●					

LEGEND


 Product rated for Interior & Exterior use
 ● Product rated for Interior use only
 † May be suitable for Exterior Floors
 * Special Order only

Merchandising materials and samples are for general reference only and representative of a product's potential characteristics. Product is subject to variation in color/shade, size, texture, and finish. Blend product from different boxes to achieve consistent shade distribution. Installer and end user must conduct a dry mock layout under proper lighting conditions to inspect the product. Installation constitutes product acceptance. Improper installation, application, use, care and maintenance voids warranty. Reference the packaging for installation guidance. We reserve the right to make product changes at any time without notice.


LAYING PATTERNS




30% Offset




50% Offset



Random



Herringbone



Square Basket

