



Antique White
100008032 - 12"x24" Field Tile - Matte



Antique White
100008035 - 24"x24" Field Tile - Matte



Antique White
100008038 - 24"x36" R11 Paver - Matte



Antique White
100008041
4"x4" Mosaic - Matte
(12"x12" Sheet)



Historic Greige
100008033 - 12"x24" Field Tile - Matte



Historic Greige
100008036 - 24"x24" Field Tile - Matte



Historic Greige
100008039 - 24"x36" R11 Paver - Matte



Historic Greige
100008042
4"x4" Mosaic - Matte
(12"x12" Sheet)



Atlas Gray
100008034 - 12"x24" Field Tile - Matte



Atlas Gray
100008037 - 24"x24" Field Tile - Matte



Atlas Gray
100008040 - 24"x36" R11 Paver - Matte







Atlas Gray
100008043
4"x4" Mosaic - Matte
(12"x12" Sheet)

Bluerun

Glazed Color Body Porcelain

Photo Features 24"x36" R11 Paver - Matte in Historic Greige.

SIZING & PACKAGING

Type	Shape	Antique White Item Code	Atlas Gray Item Code	Historic Greige Item Code	Size	Description	Pcs / Ctn	Sf / Ctn
Field		100008032	100008034	100008033	12"x24"	Rectified Field Tile - Matte	8	15.62
		100008035	100008037	100008036	24"x24"	Rectified Field Tile - Matte	4	15.58
Paver		100008038	100008040	100008039	24"x36"	R11 Paver - Matte	1	5.85
Trim		100008044	100008046	100008045	3"x24"	Bullnose - Matte	5	-
Mosaic	 ∅	100008041	100008043	100008042	12"x12" Sheet	4"x4" Mosaic - Matte	10	-

ANSI TECHNICAL SPECIFICATIONS

	DCOF Acutest	PEI Rating ASTM# C1027	Frost Resistant ASTM# C1026	Scratch Resistance MOHS	Breaking Strength ASTM# C648	Water Absorption ASTM# C373	Chemical Resistance ASTM# C650
Results	≥ 0.42	N/A	Unaffected	7	≥ 450 lbf	≤ 0.5%	Unaffected

Shade Variation



V3-Moderate

APPLICATIONS - NON PAVERS

	Floors	Walls	Countertops	Shower Floors	Shower Walls	Pools/Spas
Residential	●†	◻	◻	●†	◻	◻
Commercial	●†	◻	◻	●†	◻	◻

APPLICATIONS - R11 PAVERS

	Floors	Walls	Countertops	Shower Floors	Shower Walls	Pools/Spas
Residential	◻		◻	◻		◻
Commercial	◻		◻	◻		◻

LEGEND

- ◻ Product rated for Interior & Exterior use
- Product rated for Interior use only
- † May be suitable for Exterior Floors
- ∅ Applications & ANSI Technical Specifications do not apply
- * Special Order only



IMPORTANT: Installation Instructions - We recommend wet cutting or the score and snap method during the installation process. Improper installation techniques could expose installer to inhalation of harmful silica dust. Do not dry cut product using power tools during the installation process. Using dry cutting methods could present a risk of acute lung injury. If adequate ventilation cannot be achieved, wear a mask or respirator. For more information, see the SDS at www.bedrosians.com/en/installation-care-maintenance/.

† The TCNA does not rate products for exterior floors. Project specifier must determine product suitability for exterior floor applications by evaluating specific project conditions, type of use, traffic, drainage, expected contaminants (such as water, oil, grease, etc.), wear, maintenance, and manufacturer's specifications and guidelines. Use caution--product may not be suitable for pool decks. Not suitable for ramps. No polished tiles; only textured surfaces may be suitable.

Merchandising materials and samples are for general reference only and representative of a product's potential characteristics. Tile is subject to variation in color/shade, size, texture, and finish. Field, mosaic and trim tile may not match exactly. Blend tiles from different boxes to achieve consistent shade distribution. Installer and end user must conduct a dry mock layout under proper lighting conditions to inspect the product. Installation constitutes product acceptance. Improper installation, application, use, care and maintenance voids warranty. Reference the TCNA Handbook and ANSI for installation guidance. Please visit bedrosians.com for current product information. We reserve the right to make product changes at any time without notice.

