Bedrosians

La Jolla Engineered HDF Wood



Soledad 100007632 9"x60" 12mm Engineered HDF Wood



Bahia 100007633 9"x60" 12mm Engineered HDF Wood



Beaumont 100007627 9"x60" 12mm Engineered HDF Wood



Prospect 100007631 9"x60" 12mm Engineered HDF Wood



Cliffridge 100007630 9"x60" 12mm Engineered HDF Wood



Miramar 100007629 9"x60" 12mm Engineered HDF Wood



Nautilus 100007628 9"x60" 12mm Engineered HDF Wood



SIZING & PACKAGING

Type	Shape	Bahia Item Code	Beaumont Item Code	Cliffridge Item Code	Miramar Item Code	Nautilus Item Code	Prospect Item Code	Soledad Item Code	Size	Description	Pcs/Ctn	Sf / Ctn
Plank		100007633	100007627	100007630	100007629	100007628	100007631	100007632	9"x60"	12mm Engineered HDF Wood	7	27.13
Trim		100007745	100007739	100007742	100007741	100007740	100007743	100007744	41/2"x941/2"	8mm Flush Stair Nose	-	-

TECHNICAL SPECIFICATIONS

Description	Result
Construction	10mmWaterResistantStandardCore+2mmEVAAttachedPad
Dimensions	9.4" Wide x 60" Long, 238mm x 1515mm
Overall Thickness	12mm (Includes 2mm Pad)
Wear Surface	AC5 (5000 Cycles)
Texture	EIR
Gloss	Super Matt (5±2)
Edge Profile	4-Sided Painted Bevel
Waxing	4-Sided Waxing
Click	Unilin/Angle to Angle
Swelling Rate	≤10%
MDFDensity	880-900 kg/m3
Radiant Floor Heating	Approved
Formaldehyde Emission	CARB2 Compliant
VOC Emission	Floorscore Compliant
Residential Warranty	25 Years
Commercial Warranty	10 Years

APPLICATIONS (Rated AC5)


	Floors	Walls (Installed w/ Adhesive)	Countertops	Shower Floors	Shower Walls	Pools/Spas
Residential	•	•				
Commercial	•	•				


LEGEND

Product rated for Interior & Exterior use


- Product rated for Interior use only
- † May be suitable for Exterior Floors
- * Special Order only

LAYING PATTERNS





50% Offset



Random

Merchandising materials and samples are for general reference only and representative of a product's potential characteristics. Product is subject to variation in color/shade, size, texture, and finish. Blend product from different boxes to achieve consistent shade distribution. Installer and end user must conduct a dry mock layout under proper lighting conditions to inspect the product. Installation constitutes product acceptance. Improper installation, application, use, care and maintenance voids warranty. Reference the packaging for installation guidance. We reserve the right to make product changes at any time without notice.