

Wall Tile Sizes

---



**Blanco - BLA**  
CERWINBLA824 - 8"x24" Non-Rectified Wall Tile - Gloss



**Beige - BEI**  
CERWINBEI824 - 8"x24" Non-Rectified Wall Tile - Gloss



**Gris - GRI**  
CERWINGRI824 - 8"x24" Non-Rectified Wall Tile - Gloss



# Winter

Glazed Ceramic



Photo Features 8"x24" Non-Rectified Wall Tile - Gloss in Blanco.

## SIZING & PACKAGING

Type	Shape	Blanco	Beige	Gris	Size	Description	Pcs / Ctn	Sf / Ctn
Field		CERWINBLA824	CERWINBEI824	CERWINGRI824	8"x24"	Non-Rectified Wall Tile - Gloss	14	19.59
Trim		CERWINBLATRIM	CERWINBEITRIM	CERWINGRITRIM	1/2"x12"	Glazed Edge Trim - Gloss	-	-

## ANSI TECHNICAL SPECIFICATIONS

	DCOF Acutest	PEI Rating ASTM# C1027	Frost Resistant ASTM# C1026	Scratch Resistance MOHS	Breaking Strength ASTM# C648	Water Absorption ASTM# C373	Chemical Resistance ASTM# C650
Results	N/A	N/A	N/A	2	Pass (≥ 600 ISO)	>1.0 (Ceramic)	N/A








## APPLICATIONS

	Floors	Walls	Countertops	Shower Floors	Shower Walls	Pools/Spas
Residential		●			●	
Commercial		●			●	



## LEGEND

-  Product rated for Interior & Exterior use
-  Product rated for Interior use only
-  † May be suitable for Exterior Floors
-  Applications & ANSI Technical Specifications do not apply
-  \* Special Order only



**IMPORTANT:** Installation Instructions - We recommend wet cutting or the score and snap method during the installation process. Improper installation techniques could expose installer to inhalation of harmful silica dust. Do not dry cut product using power tools during the installation process. Using dry cutting methods could present a risk of acute lung injury. If adequate ventilation cannot be achieved, wear a mask or respirator. For more information, see the SDS at [www.bedrosians.com/en/installation-care-maintenance/](http://www.bedrosians.com/en/installation-care-maintenance/).

This tile must be installed with a premium modified thinset. Do not use mastic.

Merchandising materials and samples are for general reference only and representative of a product's potential characteristics. Tile is subject to variation in color/shade, size, texture, and finish. Field, mosaic and trim tile may not match exactly. Blend tiles from different boxes to achieve consistent shade distribution. Installer and end user must conduct a dry mock layout under proper lighting conditions to inspect the product. Installation constitutes product acceptance. Improper installation, application, use, care and maintenance voids warranty. Reference the TCNA Handbook and ANSI for installation guidance. Please visit [bedrosians.com](http://bedrosians.com) for current product information. We reserve the right to make product changes at any time without notice.

