Field Tile Sizes



Pearl - PE CRDEPIPE440 - 4"x40" CRDEPIPE840 - 8"x40"



White - WH CRDEPIWH440 - 4"x40" CRDEPIWH840 - 8"x40"



Camel - CA CRDEPICA440 - 4"x40" CRDEPICA840 - 8"x40"



Taupe - TA CRDEPITA440 - 4"x40" CRDEPITA840 - 8"x40"



Dark Brown - DB CRDEPIDB440 - 4"x40" CRDEPIDB840 - 8"x40"




SIZING & PACKAGING

| Туре | Shape | Item Code | Size | Description | Pcs / Ctn | Sf / Ctn |
|-------|-------|-------------|--------|----------------------|-----------|----------|
| Field | | CRDEPI••440 | 4"x40" | Rectified Field Tile | 10 | 10.76 |
| | | CRDEPI••840 | 8"x40" | Rectified Field Tile | 5 | 10.76 |

ANSI TECHNICAL SPECIFICATIONS

| | DCOF Acutest | PEI Rating ASTM# C1027 | Frost Resistant ASTM# C1026 | Scratch Resistance MOHS | Breaking Strength ASTM# C648 | Water Absorption ASTM# C373 | Chemical Resistance ASTM# C650 |
|---------|-----------------|------------------------------|-----------------------------------|-------------------------------|------------------------------------|-----------------------------------|--------------------------------------|
| Results | ≥ 0.42 | Pass ≤ 175 (ISO) | Unaffected | N/A | Pass (1,300 ISO) | ≤ 0.5% | Unaffected |



Shade Variation

APPLICATIONS

| | Floors | Walls | Countertops | Shower Floors | Shower Walls | Pools/Spas |
|------------------|--------|-------|-------------|---------------|--------------|------------|
| Residential | • | • | • | • | • | • |
| Light Commercial | • | • | • | • | • | • |
| Commercial | • | • | • | • | • | • |



LEGEND

- Product rated for Interior & Exterior use
- Product rated for Interior use only
- † May be suitable for Exterior Floors

- \varnothing Applications & ANSI Technical Specifications do not apply
- * Special Order only





Use of a leveling system during installation is strongly recommended















Images and product samples are representative of a product's potential characteristics. There is no guarantee that the sample product or images will 100% match the product received. Field, mosaic, and trim tile may not be an exact match. Tiles are subject to variations in color, shade, sizing, surface texture and finish. Installer must conduct a dry mock layout under proper lighting conditions prior to installation. It is the consumer's responsibility to inspect the product prior to installation to ensure satisfaction. Once installed, the product is deemed accepted. Check Manufacturer's specifications as some Mosaic tiles may not be appropriate for wet applications. Reference the most current TCNA Handbook, ANSI, Manufacturer's specifications, and Bedrosians Care & Maintenance guide for installation, outdoor use, care and maintenance information. Improper installation, application, use, care and maintenance voids warranty. We reserve the right to make changes to product specifications at any time without notice. Please visit www.bedrosians.com for current product information.

