

1/2"x2" Herringbone Mosaic - Gloss (11"x12 1/4" Sheet)



White - WHI
DEC90WHI122MO



Off White - OFW
DEC90OFW122MO



Putty - PUT
DEC90PUT122MO



Gray Haze - GRH
DEC90GRH122MO



Metallic - MET
DEC90MET122MO



Shadow - SHA
DEC90SHA122MO






90°
Decorative (Glazed Porcelain)

Photo Features 1/2"x2" Herringbone Mosaic - Gloss in White.


SIZING & PACKAGING

Type	Shape	Item Code	Size	Description	Pcs / Ctn	Sf / Ctn
Mosaic		DEC90***122MO	11"x12 1/4" Sheet	1/2"x2" Herringbone Mosaic - Gloss	10	9.40

ANSI TECHNICAL SPECIFICATIONS

	DCOF Acutest	Scratch Resistance MOHS	Breaking Strength ASTM# C648	Water Absorption ASTM# C373	Chemical Resistance ASTM# C650	Bond Strength A137.2-7.7	Thermal Shock ASTM# C484
Results	N/A	7	N/A	≤ 0.5%	Unaffected	N/A	N/A

Shade Variation



V2-Slight

APPLICATIONS

	Floors	Walls	Countertops	Shower Floors	Shower Walls	Pools/Spas
Residential	•	◻	◻		◻	
Commercial		◻	◻		◻	



LEGEND

- ◻ Product rated for Interior & Exterior use
- Product rated for Interior use only
- † May be suitable for Exterior Floors
- ◊ Applications & ANSI Technical Specifications do not apply
- * Special Order only



The mesh backing on this tile has minimal glue to allow greater thinset coverage. To prevent the mosaics from falling off the mesh, keep the sheets as dry as possible while cutting. If necessary, place a light clear adhesive tape over the sheet while cutting to avert water. Install full sheets as much as possible. Fully embed 1/3 thickness of the tiles into the premium modified thinset.

Do not use chlorine, acids, or other harsh chemicals to clean.

Merchandising materials and samples are for general reference only and representative of a product's potential characteristics. Tile is subject to variation in color/shade, size, texture, and finish. Field, mosaic and trim tile may not match exactly. Blend tiles from different boxes to achieve consistent shade distribution. Installer and end user must conduct a dry mock layout under proper lighting conditions to inspect the product. Installation constitutes acceptance of the product. Reference the TCNA, ANSI, Manufacturer's specifications, and Bedrosians Care & Maintenance Guide. Improper installation, application, use, care and maintenance voids warranty. We reserve the right to make product changes without notice. Please visit bedrosians.com for current product information.

