



Early Grey - EAG  
DECAVOEAG28 - Brick



Sidewalk - SID  
DECAVOSID28 - Standard Brick



Used Red - USR  
DECAVOUSR28 - Antik Brick







# Avondale

## Decorative (Brick)

Photo Features 2"x8" Brick - Matte in Early Grey.


### SIZING & PACKAGING

Type	Shape	Item Code	Size	Description	Pcs / Ctn	Sf / Ctn
Field		DECAVOUSR28	2"x8"	Antik Brick - Matte (Used Red Brick)	72	11.08
		DECAVOEAG28	2"x8"	Brick - Matte (Early Gray - Signature Color)	66	9.43
		DECAVOSID28	2"x8"	Standard Brick - Matte (Sidewalk - Premium Color)	66	9.43

### ANSI TECHNICAL SPECIFICATIONS

	DCOF Acutest	PEI Rating ASTM# C1027	Frost Resistant ASTM# C1026	Scratch Resistance MOHS	Breaking Strength ASTM# C648	Water Absorption ASTM# C373	Chemical Resistance ASTM# C650
Results	≥ 0.42	N/A	Unaffected	7	≥ 250 lbf	> 1.0 (Ceramic)	Unaffected

#### Shade Variation



V3-Moderate

### APPLICATIONS

	Floors	Walls	Countertops	Shower Floors	Shower Walls	Pools/Spas
Residential	● †	■	■			
Commercial	● †	■	■			



Made in USA

### LEGEND

- Product rated for Interior & Exterior use
- Product rated for Interior use only
- † May be suitable for Exterior Floors
- Ø Applications & ANSI Technical Specifications do not apply
- \* Special Order only

This product may be installed near or on the face of high-heat areas, but not inside. This product cannot be installed in showers, pools, spas, or waterline applications. Do not use chlorine, acids, or other harsh chemicals to clean. Use only sanded grout with this product. This handmade product may vary in sizing. Use a minimum 1/2" grout joint. Brick tiles must be sealed before and after grouting to prevent penetration. Seal grout joints as well. For a low sheen, Master Seal 100 by Desert Brand is the recommended topical sealer. For a matte finish, use a high quality penetrating sealer. All spills must be cleaned immediately to prevent staining. These tiles are handmade and subject to color variation. Mix randomly from different boxes to balance variation. Wet the back of the tile prior to setting. Apply mortar to both the substrate and the back of the brick tile using a 1/2" notched trowel.

Merchandising materials and samples are for general reference only and representative of a product's potential characteristics. Tile is subject to variation in color/shade, size, texture, and finish. Field, mosaic and trim tile may not match exactly. Blend tiles from different boxes to achieve consistent shade distribution. Installer and end user must conduct a dry mock layout under proper lighting conditions to inspect the product. Installation constitutes acceptance of the product. Reference the TCNA, ANSI, Manufacturer's specifications, and Bedrosians Care & Maintenance Guide. Improper installation, application, use, care and maintenance voids warranty. We reserve the right to make product changes without notice. Please visit [bedrosians.com](https://www.bedrosians.com) for current product information.

