

Rectified Field Tile Sizes



Canvas - CAN
DOLCHACAN1224 - 12"x24" Honed
DOLCHACAN2424 - 24"x24" Honed



Smoke - SMO
DOLCHASMO1224 - 12"x24" Honed
DOLCHASMO2424 - 24"x24" Honed



Tobacco - TOB
DOLCHATOB1224 - 12"x24" Honed
DOLCHATOB2424 - 24"x24" Honed



Ocean - OCE
DOLCHAOCE1224 - 12"x24" Honed
DOLCHAOCE2424 - 24"x24" Honed



Midnight - MID
DOLCHAMID1224 - 12"x24" Honed
DOLCHAMID2424 - 24"x24" Honed

4"x8" Non-Rectified Glazed Ceramic Wall Tile - Honed



Canvas - CAN
DOLCHACAN48



Smoke - SMO
DOLCHASMO48



Tobacco - TOB
DOLCHATOB48



Ocean - OCE
DOLCHAOCE48



Midnight - MID
DOLCHAMID48

2"x2" Mosaic - Honed (12"x12" Sheet)



Canvas - CAN
DOLCHACAN22MO



Smoke - SMO
DOLCHASMO22MO



Tobacco - TOB
DOLCHATOB22MO



Ocean - OCE
DOLCHAOCE22MO



Midnight - MID
DOLCHAMID22MO

Deco Patterns - Honed



DOLCHADIA1212CASM
12"x12" Diamond Deco
Canvas, Smoke & Midnight



DOLCHAFIO1212CAOC
12"x12" Fiore Deco
Canvas & Ocean



DOLCHAFIO1212CASM
12"x12" Fiore Deco
Canvas & Smoke



DOLCHAFIO1212MICA
12"x12" Fiore Deco
Canvas & Midnight



Chateau

Glazed Color Body Porcelain

Photo Features 12"x12" Diamond Deco - Honed in Canvas, Smoke & Midnight.


SIZING & PACKAGING

Type	Shape	Item Code	Size	Description	Pcs / Ctn	Sf / Ctn
Field		∅ DOLCHA***48	4"x8"	Non-Rectified Glazed Ceramic Wall Tile - Honed	32	6.89
		DOLCHA***1224	12"x24"	Rectified Field Tile - Honed	8	15.75
		DOLCHA***2424	24"x24"	Rectified Field Tile - Honed	4	15.83
Decos		DOLCHADIA1212CASM	12"x12"	Diamond Deco - Canvas, Smoke & Midnight - Honed	10	-
		DOLCHAFIO1212MICA	12"x12"	Fiore Deco - Canvas and Midnight - Honed	10	-
		DOLCHAFIO1212CAOC	12"x12"	Fiore Deco - Canvas and Ocean - Honed	10	-
		DOLCHAFIO1212CASM	12"x12"	Fiore Deco - Canvas and Smoke - Honed	10	-
Trim		DOLCHA***312BN	3"x12"	Bullnose - Honed	15	-
		∅ DOLCHA***48BN	4"x8"	Non-Rectified Glazed Ceramic Bullnose - Honed	12	-
Mosaic		∅ DOLCHA***22MO	12"x12" Sheet	2"x2" Mosaic - Honed	-	-

ANSI TECHNICAL SPECIFICATIONS

	DCOF Acutest	PEI Rating ASTM# C1027	Frost Resistant ASTM# C1026	Scratch Resistance MOHS	Breaking Strength ASTM# C648	Water Absorption ASTM# C373	Chemical Resistance ASTM# C650
Results (Glazed Color Body Porcelain)	≥ 0.42	4	Unaffected	7	≥ 350 lbf	≤ 0.5%	Unaffected
Results (Non-Rectified Glazed Ceramic)	N/A	N/A	N/A	N/A	N/A	> 10%	N/A

Shade Variation




APPLICATIONS - Glazed Color Body Porcelain

	Floors	Walls	Countertops	Shower Floors	Shower Walls	Pools/Spas
Residential	•	◻	◻	•	◻	◻
Commercial	•	◻	◻	•	◻	◻


APPLICATIONS - Non-Rectified Glazed Ceramic

	Floors	Walls	Countertops	Shower Floors	Shower Walls	Pools/Spas
Residential		•				
Commercial		•				



LEGEND

- ◻ Product rated for Interior & Exterior use
- Product rated for Interior use only
- ∅ Applications & ANSI Technical Specifications do not apply
- * Special Order only
- † May be suitable for Exterior Floors



It is recommended to install deco tiles without an offset.

Merchandising materials and samples are for general reference only and representative of a product's potential characteristics. Tile is subject to variation in color/shade, size, texture, and finish. Field, mosaic and trim tile may not match exactly. Blend tiles from different boxes to achieve consistent shade distribution. Installer and end user must conduct a dry mock layout under proper lighting conditions to inspect the product. Installation constitutes product acceptance. Improper installation, application, use, care and maintenance voids warranty. Reference the TCNA Handbook and ANSI for installation guidance. Please visit bedrosians.com for current product information. We reserve the right to make product changes at any time without notice.

MKTTDOLCHA
REV. 7.2021

bedrosians.com

