
Wall Tile Sizes



Bianco - BI DOLGRABI412 - 4"x12" Non-Rectified Wall Tile - Gloss



Sabbia - SA DOLGRASA412 - 4"x12" Non-Rectified Wall Tile - Gloss



Ecru - EC
DOLGRAEC412 - 4"x12" Non-Rectified Wall Tile - Gloss



Panna - PA
DOLGRAPA412 - 4"x12" Non-Rectified Wall Tile - Gloss



Grigio - GR
DOLGRAGR412 - 4"x12" Non-Rectified Wall Tile - Gloss



Moka - MO DOLGRAMO412 - 4"x12" Non-Rectified Wall Tile - Gloss




SIZING & PACKAGING

| Туре | Shape | Item Code | Size | Description | Pcs / Ctn | Sf / Ctn |
|----------|-------|----------------|--------|---------------------------------|-----------|----------|
| WallTile | | DOLGRA•••412 | 4"x12" | Non-Rectified Wall Tile - Gloss | 34 | 10.98 |
| Trim | | DOLGRA•••412BN | 4"x12" | Surface Bullnose - Gloss | 12 | - |

ANSI TECHNICAL SPECIFICATIONS

| | DCOF Acutest | PEI Rating ASTM# C1027 | Frost Resistant ASTM# C1026 | Scratch Resistance MOHS | Breaking Strength ASTM# C648 | Water Absorption ASTM# C373 | Chemical Resistance ASTM#C650 |
|---------|-----------------|------------------------------|-----------------------------------|-------------------------------|------------------------------------|-----------------------------------|-------------------------------------|
| Results | N/A | N/A | N/A | N/A | Pass (R≥15N/mm2ISO) | > 1.0(Ceramic) | Unaffected |

Shade Variation



V2-Slight

APPLICATIONS

| | Floors | Walls | Countertops | Shower Floors | Shower Walls | Pools/Spas |
|-------------|--------|-------|-------------|---------------|--------------|------------|
| Residential | | • | | | • | |
| Commercial | | • | | | • | |

LEGEND

- Product rated for Interior & Exterior use
- Product rated for Interior use only
- † May be suitable for Exterior Floors

- Applications & ANSI Technical Specifications do not apply
- * Special Order only









This tile must be installed with a premium modified thinset. Do not use mastic.

Merchandising materials and samples are for general reference only and representative of a product's potential characteristics. Tile is subject to variation in color/shade, size, texture, and finish. Field, mosaic and trim tile may not match exactly. Blend tiles from different boxes to achieve consistent shade distribution. Installer and end user must conduct a dry mock layout under proper lighting conditions to inspect the product. Installation constitutes product acceptance. Improper installation, application, use, care and maintenance voids warranty. Reference the TCNA Handbook and ANSI for installation guidance. Please visit bedrosians.com for current product information. We reserve the right to make product changes at any time without notice.

