

Field Tile Sizes



Brillante - BR
DOLMATBR1224 - 12"x24" Non-Rectified Field Tile - Honed
DOLMATBR1836 - 18"x36" Non-Rectified Field Tile



Classica - CL
DOLMATCL1224 - 12"x24" Non-Rectified Field Tile - Honed
DOLMATCL1836 - 18"x36" Non-Rectified Field Tile - Honed



Azzurra - AZ
DOLMATAZ1224 - 12"x24" Non-Rectified Field Tile - Honed
DOLMATAZ1836 - 18"x36" Non-Rectified Field Tile - Honed



Tabacco - TA
DOLMATTA1224 - 12"x24" Non-Rectified Field Tile - Honed
DOLMATTA1836 - 18"x36" Non-Rectified Field Tile - Honed



Unica - UN
DOLMATUN1224 - 12"x24" Non-Rectified Field Tile - Honed
DOLMATUN1836 - 18"x36" Non-Rectified Field Tile - Honed

2"x2" Mosaic - Honed (12"x12" Sheet)



Brillante - BR
DOLMATBR22MO



Classica - CL
DOLMATCL22MO



Azzurra - AZ
DOLMATAZ22MO



Tabacco - TA
DOLMATTA22MO



Unica - UN
DOLMATUN22MO



Matita

Glazed Color Body Porcelain

Photo Features 18"x36" Non-Rectified Field Tile - Honed in Classica.


SIZING & PACKAGING

Type	Shape	Item Code	Size	Description	Pcs / Ctn	Sf / Ctn
Field		DOLMAT-1224	12"x24"	Non-Rectified Field Tile - Honed	8	15.75
		DOLMAT-1836	18"x36"	Non-Rectified Field Tile - Honed	5	22.19
Trim		DOLMAT-324BN	3"x24"	Bullnose - Honed	16	7.79
Mosaic		∅ DOLMAT-22MO	12"x12" Sheet	2"x2" Mosaic - Honed	5	-

ANSI TECHNICAL SPECIFICATIONS

	DCOF Acutest	PEI Rating ASTM# C1027	Frost Resistant ASTM# C1026	Scratch Resistance MOHS	Breaking Strength ASTM# C648	Water Absorption ASTM# C373	Chemical Resistance ASTM# C650
Results	≥ 0.42	Pass ≤ 175 (ISO)	Unaffected	7	≥ 250 lbf	≤ 0.5%	Unaffected


Shade Variation



V2-Slight

APPLICATIONS

	Floors	Walls	Countertops	Shower Floors	Shower Walls	Pools/Spas
Residential	●	◻	◻	●	◻	◻
Commercial	●	◻	◻	●	◻	◻



LEGEND

- ◻ Product rated for Interior & Exterior use
- Product rated for Interior use only
- † May be suitable for Exterior Floors
- ∅ Applications & ANSI Technical Specifications do not apply
- * Special Order only



Use of a leveling system during installation is strongly recommended

Merchandising materials and samples are for general reference only and representative of a product's potential characteristics. Tile is subject to variation in color/shade, size, texture, and finish. Field, mosaic and trim tile may not match exactly. Blend tiles from different boxes to achieve consistent shade distribution. Installer and end user must conduct a dry mock layout under proper lighting conditions to inspect the product. Installation constitutes product acceptance. Improper installation, application, use, care and maintenance voids warranty. Reference the TCNA Handbook and ANSI for installation guidance. Please visit bedrosians.com for current product information. We reserve the right to make product changes at any time without notice.

