

Field Tile Size

---



**Classico - CL**  
DOLTOSCL1224  
12"x24" Non-Rectified Field Tile - Honed



**Silver - SI**  
DOLTOSSI1224  
12"x24" Non-Rectified Field Tile - Honed



**Grigio - GR**  
DOLTOSGR1224  
12"x24" Non-Rectified Field Tile - Honed

2"x2" Mosaic - Honed (12"x12" Sheet)

---



**Classico - CL**  
DOLTOSCL22MO



**Silver - SI**  
DOLTOSSI22MO



**Grigio - GR**  
DOLTOSGR22MO

1"x4" Herringbone Mosaic - Honed (12"x12" Sheet)

---



**Classico - CL**  
DOLTOSCL14MO



**Silver - SI**  
DOLTOSSI14MO




**Grigio - GR**  
DOLTOSGR14MO

# Toscano

Glazed Porcelain

Photo Features 12"x24" Non-Rectified Field Tile - Honed in Grigio.


## SIZING & PACKAGING

Type	Shape	Item Code	Size	Description	Pcs / Ctn	Sf / Ctn
Field		DOLTOS•1224	12"x24"	Non-Rectified Field Tile - Honed	8	15.75
Trim		DOLTOS•312BN	3"x12"	Surface Bullnose - Honed	15	-
Mosaic		Ø DOLTOS•14MO	12"x12" Sheet	1"x4" Herringbone Mosaic	5	4.59
		Ø DOLTOS•22MO	12"x12" Sheet	2"x2" Mosaic - Honed	5	-

## ANSI TECHNICAL SPECIFICATIONS


	DCOF Acutest	PEI Rating ASTM# C1027	Frost Resistant ASTM# C1026	Scratch Resistance MOHS	Breaking Strength ASTM# C648	Water Absorption ASTM# C373	Chemical Resistance ASTM# C650
Results	≥ 0.42	N/A	Unaffected	N/A	≥ 350 lbf	≤ 0.5%	Unaffected

### Shade Variation




## APPLICATIONS

	Floors	Walls	Countertops	Shower Floors	Shower Walls	Pools/Spas
Residential	•	•	•	•	•	•
Commercial	•	•	•	•	•	•



## LEGEND

- Product rated for Interior & Exterior use
- Product rated for Interior use only
- † May be suitable for Exterior Floors
- Ø Applications & ANSI Technical Specifications do not apply
- \* Special Order only



Merchandising materials and samples are for general reference only and representative of a product's potential characteristics. Tile is subject to variation in color/shade, size, texture, and finish. Field, mosaic and trim tile may not match exactly. Blend tiles from different boxes to achieve consistent shade distribution. Installer and end user must conduct a dry mock layout under proper lighting conditions to inspect the product. Installation constitutes product acceptance. Improper installation, application, use, care and maintenance voids warranty. Reference the TCNA Handbook and ANSI for installation guidance. Please visit [bedrosians.com](http://bedrosians.com) for current product information. We reserve the right to make product changes at any time without notice.

