Napa Glazed Porcelain



Chestnut



FLONAPCH624 - 6" x 24"

Grey



FLONAPGR624 - 6" x 24"

Oak



FLONAPOA624 - 6" x 24"

Walnut



FLONAPWA624 - 6" x 24"

Honey



FLONAPHO624 - 6" x 24"

Sizes




Tile Thickness: 3/8"

Packaging

Туре	Size	Item Code	Pcs / Ctn	Sf / Ctn	Ctn / Plt	Sf / PIt
Field Tile	6"x24"	FLONAP••624	12	12.00	48	576.00

Applications	Floors	Walls	Countertops	Showers Floors	Showers Walls	Pools
Residential	•	•	•	•	•	
Light Commercial	•	•	•	•	•	
Commercial	•	•	•	•	•	
Legend: Product rated for interior & exterior use				r use only		







Technical Specifications	Results	ASTM#	
Water Absorption	≤ 0.50%	C373	
PEI Rating	3	C1027	
Scratch Resistance	7	MOHS	
Frost Resistant	Unaffected	C1026	
DCOF Acutest	≥ 0.42	N/A	
Breaking Strength	≥ 250 lbs	C648	
Chemical Resistant	Unaffected	C650	













Do not install in pools, spas/hot tubs, and/or submerged applications.

The maximum allowable installation offset is 33%. Minimum grout joint must be 3/16 inch. Please refer to the most current TCNA Handbook. Manufacturer strongly recommends use of a leveling system during installation.

Images and product samples are representative of a product's potential characteristics. There is no guarantee that the sample product or images will 100% match the product received. Field and trim tile may not be an exact match. We reserve the right to make charges to product specifications at any time without notice. Tiles are subject to variations in color, shade, sizing, surface texture and finish. Prior to installation, installer must blend tiles from several different boxes to achieve an even distribution of color range. Installer must conduct a dry mock layout under proper lighting conditions prior to installation. It is the consumer's responsibility to inspect the product prior to installation to ensure satisfaction. Once installed, the product is deemed accepted. Beference the most current TOAN Handbook, ANSI, manufacturer's specifications, and the Bedrosians Care & Maintenance guide for installation, outdoor use, care and maintenance information. Improper installation, application, and/or use voids warranty. Please visit www.bedrosians.com for current product information.