


Field Tile Sizes



Snow - SNO
FLOPLASNO1224
12"x24" Non-Rectified Field Tile - Matte



Sisal - SIS
FLOPLASIS1224
12"x24" Non-Rectified Field Tile - Matte



Seashell - SEA
FLOPLASEA1224
12"x24" Non-Rectified Field Tile - Matte



Mist - MIS
FLOPLAMIS1224
12"x24" Non-Rectified Field Tile - Matte

1"x4" Mosaic - Matte (12"x12" Sheet)



Snow
100000234



Sisal
100000235



Seashell
100000236



Mist
100000237



Photo Features 12"x24" Non-Rectified Field Tile - Matte in Mist.



Plaza

Glazed Porcelain


Photo Features 12"x24" Non-Rectified Field Tile - Matte in Snow and Mist.

SIZING & PACKAGING

Type	Shape	Item Code	Size	Description	Pcs / Ctn	Sf / Ctn
Field		FLOPLA***1224	12"x24"	Non-Rectified Field Tile - Matte	8	16.00
Trim		FLOPLA***3X24BN	3"x24"	Bullnose - Matte	10	-
Mosaic		Ø 100000234	12"x12" Sheet	1"x4" Mosaic - Matte in Snow	5	-
		Ø 100000235	12"x12" Sheet	1"x4" Mosaic - Matte in Sisal	5	-
		Ø 100000236	12"x12" Sheet	1"x4" Mosaic - Matte in Seashell	5	-
		Ø 100000232	12"x12" Sheet	1"x4" Mosaic - Matte in Mist	5	-


ANSI TECHNICAL SPECIFICATIONS

	DCOF Acutest	PEI Rating ASTM# C1027	Frost Resistant ASTM# C1026	Scratch Resistance MOHS	Breaking Strength ASTM# C648	Water Absorption ASTM# C373	Chemical Resistance ASTM# C650
Results	≥ 0.42	4	Unaffected	6	≥ 400 lbf	≤ 0.5%	Unaffected




APPLICATIONS

	Floors	Walls	Countertops	Shower Floors	Shower Walls	Pools/Spas
Residential	•	◻	◻	•	◻	◻
Commercial	•	◻	◻	•	◻	◻



LEGEND

- ◻ Product rated for Interior & Exterior use
- Product rated for Interior use only
- † May be suitable for Exterior Floors
- ◊ Applications & ANSI Technical Specifications do not apply
- * Special Order only



Merchandising materials and samples are for general reference only and representative of a product's potential characteristics. Tile is subject to variation in color/shade, size, texture, and finish. Field, mosaic and trim tile may not match exactly. Blend tiles from different boxes to achieve consistent shade distribution. Installer and end user must conduct a dry mock layout under proper lighting conditions to inspect the product. Installation constitutes product acceptance. Improper installation, application, use, care and maintenance voids warranty. Reference the TCNA Handbook and ANSI for installation guidance. Please visit bedrosians.com for current product information. We reserve the right to make product changes at any time without notice.

