

Field Tile Sizes




White - WHI
FLOTESWHI1224
12"x24" Non-Rectified Field Tile - Pressed



Beige - BEI
FLOTESBEI1224
12"x24" Non-Rectified Field Tile - Pressed



Light Grey - LIG
FLOTESLIG1224
12"x24" Non-Rectified Field Tile - Pressed



Taupe - TAU
FLOTETAU1224
12"x24" Non-Rectified Field Tile - Pressed

2"x2" Mosaic - Matte (12"x12" Sheet)



White - WHI
FLOTESWHIMOS2X2



Beige - BEI
FLOTESBEIMOS2X2



Light Grey - LIG
FLOTESLIGMOS2X2



Taupe - TAU
FLOTETAUMOS2X2





Tesoro

Glazed Porcelain

Photo Features 12"x24" Non-Rectified Field Tile - Pressed & 2"x2" Mosaic - Matte in White.


SIZING & PACKAGING

| Type | Shape | Item Code | Size | Description | Pcs / Ctn | Sf / Ctn |
|--------|-------|-------------------|---------------|------------------------------------|-----------|----------|
| Field | | FLOTES***1224 | 12"x24" | Non-Rectified Field Tile - Pressed | 8 | 16.00 |
| Trim | | FLOTES***3X24BN | 3"x24" | Bullnose - Matte | 10 | - |
| Mosaic | | ∅ FLOTES***MOS2X2 | 12"x12" Sheet | 2"x2" Mosaic - Matte | 5 | - |

ANSI TECHNICAL SPECIFICATIONS

| | DCOF Acutest | PEI Rating ASTM# C1027 | Frost Resistant ASTM# C1026 | Scratch Resistance MOHS | Breaking Strength ASTM# C648 | Water Absorption ASTM# C373 | Chemical Resistance ASTM# C650 |
|---------|--------------|------------------------|-----------------------------|-------------------------|------------------------------|-----------------------------|--------------------------------|
| Results | ≥ 0.42 | 4 | Unaffected | 6 | ≥ 400 lbf | ≤ 0.5% | Unaffected |


Shade Variation



V3-Moderate


APPLICATIONS

| | Floors | Walls | Countertops | Shower Floors | Shower Walls | Pools/Spas |
|-------------|--------|-------|-------------|---------------|--------------|------------|
| Residential | • | ◻ | ◻ | • | ◻ | ◻ |
| Commercial | • | ◻ | ◻ | • | ◻ | ◻ |



LEGEND

- ◻ Product rated for Interior & Exterior use
- Product rated for Interior use only
- † May be suitable for Exterior Floors
- ∅ Applications & ANSI Technical Specifications do not apply
- * Special Order only



Use of a leveling system during installation is strongly recommended

Merchandising materials and samples are for general reference only and representative of a product's potential characteristics. Tile is subject to variation in color/shade, size, texture, and finish. Field, mosaic and trim tile may not match exactly. Blend tiles from different boxes to achieve consistent shade distribution. Installer and end user must conduct a dry mock layout under proper lighting conditions to inspect the product. Installation constitutes product acceptance. Improper installation, application, use, care and maintenance voids warranty. Reference the TCNA Handbook and ANSI for installation guidance. Please visit bedrosians.com for current product information. We reserve the right to make product changes at any time without notice.

