

Field Tile Sizes



Ivory - IVO
MIRWATIVO1224 - 12"x24" Non-Rectified - Matte



Beige - BEI
MIRWATBEI1224 - 12"x24" Non-Rectified - Matte



Grey - GRE
MIRWATGRE1224 - 12"x24" Non-Rectified - Matte



Tobacco - TOB
MIRWATTOB1224 - 12"x24" Non-Rectified - Matte

2"x2" Mosaic - Matte (12"x12" Sheet)



Ivory - IVO
MIRWATIVO22MO



Beige - BEI
MIRWATBEI22MO



Grey - GRE
MIRWATGRE22MO



Tobacco - TOB
MIRWATTOB22MO



Watermark

Glazed Porcelain

Photo Features 12"x24" Non-Rectified Field Tile - Matte in Grey.


SIZING & PACKAGING

Type	Shape	Item Code	Size	Description	Pcs / Ctn	Sf / Ctn
Field		MIRWAT***1224	12"x24"	Non-Rectified Field Tile - Matte	7	14.01
Trim		MIRWAT***324BN	3"x24"	Bullnose - Matte	10	-
Mosaic		Ø MIRWAT***22MO	12"x12" Sheet	2"x2" Mosaic - Matte	5	-

ANSI TECHNICAL SPECIFICATIONS


	DCOF Acutest	PEI Rating ASTM# C1027	Frost Resistant ASTM# C1026	Scratch Resistance MOHS	Breaking Strength ASTM# C648	Water Absorption ASTM# C373	Chemical Resistance ASTM# C650
Results	≥ 0.42	4	Unaffected	6	≥ 350 lbf	≤ 0.5%	Unaffected

Shade Variation



APPLICATIONS

	Floors	Walls	Countertops	Shower Floors	Shower Walls	Pools/Spas
Residential	●	◐	◐	●	◐	◐
Commercial	●	◐	◐	●	◐	◐




LEGEND

- ◐ Product rated for Interior & Exterior use
- Product rated for Interior use only
- † May be suitable for Exterior Floors
- Ø Applications & ANSI Technical Specifications do not apply
- * Special Order only



PRODUCT CERTIFIED
FOR LOW CHEMICAL
EMISSIONS.
UL.COM/IGG
UL 2818



Use of a leveling system during installation is strongly recommended

Minimum grout joint must be 3/16 inch. Please refer to the most current TCNA Handbook for installation guidelines.

Merchandising materials and samples are for general reference only and representative of a product's potential characteristics. Tile is subject to variation in color/shade, size, texture, and finish. Field, mosaic and trim tile may not match exactly. Blend tiles from different boxes to achieve consistent shade distribution. Installer and end user must conduct a dry mock layout under proper lighting conditions to inspect the product. Installation constitutes product acceptance. Improper installation, application, use, care and maintenance voids warranty. Reference the TCNA Handbook and ANSI for installation guidance. Please visit bedrosians.com for current product information. We reserve the right to make product changes at any time without notice.

