Bedrosians[®] Tile & Stone

Mexican Saltillo Pavers

Unglazed Saltillo Clay Tile

Field Tile - Matte



SAL1212 - 111/2"x111/2" Mexican Saltillo Pavers - Matte



SAL1212S - 11 1/2" x11 1/2" Mexican Saltillo Pavers - Sealed - Matte



SALSUP1212 - 11 1/2"x11 1/2" Super Saltillo Pavers - Matte




SALSUP1212S - 111/2"x111/2" Super Saltillo Pavers - Sealed - Matte


SIZING & PACKAGING

Туре	Shape	Item Code	Size	Description	Pcs/Ctn	Sf/Ctn
Field		SAL1212	111/2"x111/2"	Mexican Saltillo Pavers - Matte	11	10.23
		SAL1212S	111/2"x111/2"	Mexican Saltillo Pavers - Sealed - Matte	11	10.23
		SALSUP1212	111/2"x111/2"	Super Saltillo Pavers - Matte	11	10.23
		SALSUP1212S	11 1/2"x11 1/2"	Super Saltillo Pavers - Sealed - Matte	11	10.23

ANSITECHNICAL SPECIFICATIONS

DCOF Acutest	PEI Rating ASTM# C1027	Frost Resistant ASTM# C1026	Scratch Resistance MOHS	Breaking Strength ASTM# C648	Water Absorption ASTM# C373	Chemical Resistance ASTM# C650	
N/A	N/A	N/A	N/A	N/A	> 1.0 (Saltillo)	N/A	
S							
	Floors	Walls	Countertops	Shower Floors	Shower Walls	Pools/Spas	
	•	•					
		•					
Product rated for Interior & Exterior use Product rated for Interior use only						† May be suitable for Exterior Floo	
. 101 111101101 0 2							
	N/A S	DCOF Acutest ASTM# C1027 N/A N/A S Floors	DCOF Acutest ASTM# C1027 ASTM# C1026 N/A N/A N/A N/A S Floors Walls •	DCOF Acutest ASTM# C1027 ASTM# C1026 MOHS N/A N/A N/A N/A N/A S Floors Walls Countertops • • •	DCOF Acutest ASTM# C1027 ASTM# C1026 Resistance MOHS ASTM# C648 N/A N/A N/A N/A N/A N/A N/A S Floors Walls Countertops Shower Floors	DCOF Acutest ASTM#C1027 Resistant ASTM#C1026 MOHS ASTM#C648 ASTM#C373 N/A N/A N/A N/A N/A N/A N/A N/A N/A >1.0(Saltillo) S Floors Walls Countertops Shower Floors Shower Walls • •	







Use of a leveling sectain during inertals to a leveling increased of

 $Saltillo\ tiles\ are\ not\ suitable\ for\ exterior\ applications\ and\ must\ be\ sealed\ prior\ to\ installation.$

Merchandising materials and samples are for general reference only and representative of a product's potential characteristics. Tile is subject to variation in color/shade, size, texture, and finish. Field, mosaic and trim tile may not match exactly. Blend tiles from different boxes to achieve consistent shade distribution. Installer and end user must conduct a dry mock layout under proper lighting conditions to inspect the product. Installation constitutes product acceptance. Improper installation, use, care and maintenance voids warranty. Reference the TCNA Handbook and ANSI for installation guidance. Please visit bedrosians.com for current product information. We reserve the right to make product changes at any time without notice.