





SLTANDBLK1212G - 12"x12" Gauged SLTANDBLK1224G - 12"x24" Gauged SLTANDBLK1216G - 16"x16" Gauged SLTANDBLK2424G - 24"x24" Gauged



SLTANDBLKLED 6"x24" Ledger - Natural Cleft



SLTANDBLKLEDCNR 6"x24" Ledger Corner - Natural Cleft



Andhra Black Natural Stone (Slate)

SIZING & PACKAGING

Туре	Shape	Item Code	Size	Description	Pcs/Ctn	Sf / Ctn
Field		SLTANDBLK1212G	12"x12"	Field Tile - Gauged	-	-
		SLTANDBLK1616G	16"x16"	Field Tile - Gauged	-	-
		SLTANDBLK1224G	12"x24"	Field Tile - Gauged	-	-
		SLTANDBLK2424G	24"x24"	Field Tile - Gauged	-	-
Ledger		SLTANDBLKLEDCNR	6"x24"	Ledger Corner - Natural Cleft	-	-
		SLTANDBLKLED	6"x24"	Ledger - Natural Cleft	-	-

APPLICATIONS

	Floors (Textured Only)	Walls	Countertops	Shower Floors (Textured Only)	Shower Walls	Pools/Spas
Residential	•†		۲	•†	٠	
Light Commercial	•†	•	۲	•†	•	
Commercial	•†	٠	٠	• [†]	•	

LEGEND

- Product rated for Interior & Exterior use
- Ø Applications & ANSI Technical Specifications do not apply

Product rated for Interior use only
* Special Order only

† May be suitable for Exterior Floors

Photo Features Slat



Shade Variation

V4-High

w Stand

Slate has a natural cleft rather than a smooth surface and an array of colors/shading. The foliated layers on slate tend to naturally and temporarily flake post installation as the stone settles, sometimes exposing different colors and textures. Exposure of slate to moisture, water, acid, bleach, or iron may result in oxidizing, rusting, staining or discoloration over time.

† The TCNA does not rate products for exterior floors. Project specifier must determine product suitability for exterior floor applications by evaluating specific project conditions, type of use, traffic, drainage, expected contaminants (such as water, oil, grease, etc.), wear, maintenance, and manufacturer's specifications and guidelines. Use caution--product may not be suitable for pool decks or ramps. No polished tiles; only textured surfaces may be suitable.

Merchandising materials and samples are for general reference only and representative of a product's potential characteristics. Natural stone has inherent variation in color/shade, size, texture, finish, veining, grain, movement and pitting. Blend tiles from different boxes to achieve consistent shade distribution. Installer and end user must conduct a dry mock layout under proper lighting conditions to inspect the product. Installation constitutes product acceptance. Ensure proper installation, application, use, care and maintenance. Natural stone must be sealed prior to installation. Do not use aerosol catalyst adhesives. Only use pH neutral cleaners. Natural stone may experience changes in color and finish if installed in an exterior application. There is no warranty for natural stone. Reference the TCNA Handbook and ANSI for installation guidance. Please visit bedrosians.com for current product information. We reserve the right to make product changes at any time without notice.



