


## Available Sizes



SLTBUTSCO1212G - 12"x12" Gauged SLTBUTSCO1616G - 16"x16" Gauged SLTBUTSCO2424G - 24"x24" Gauged



SLTBUTSCO0306T 3"x6" - Tumbled



SLTBUTSCO0606T 6"x6" - Tumbled



SLTBUTSCO0404T 4"x4" - Tumbled



SLTBUTSCO0202MT 2"x2" Mosaic - Tumbled (12"x12" Sheet)



SLTBUTSCOLNR Skyline Linear Mosaic - Tumbled (11 3/8"x12 1/4" Sheet)



SLTBUTSCOCHAIR 2"x12" Chair Rail Molding - Honed





SLTBUTSCOSF 6"x24" Split Face Ledger - Natural Cleft



SLTBUTSCOSFCNR 6"x24" Split Face Corner - Natural Cleft



SLTBUTSCORMM Random Mosaic Mount - Natural Cleft



SLTBUTSCOLED 6"x24" Ledger - Natural Cleft



SLTBUTSCOLEDCNR 6"x24" Ledger Corner - Natural Cleft



SLTBUTSCOCAP 12"x24"x2" Thick Wall Cap - Natural Cleft



SLTBUTSCOFLAG Flagstone - Natural Cleft (Pallet= 1 Ton, 180-200 Sq. Ft. per Pallet)




## SIZING & PACKAGING

Туре	Shape	Item Code	Size	Description	Pcs / Ctn	Sf / Ctn
Field		SLTBUTSCO0306T	3"x6"	Field Tile - Tumbled	-	-
		SLTBUTSCO0404T	4"x4"	Field Tile - Tumbled	-	-
		SLTBUTSCO0606T	6"x6"	Field Tile - Tumbled	-	-
		SLTBUTSCO1212G	12"x12"	Field Tile - Gauged	-	-
		SLTBUTSCO1616G	16"x16"	Field Tile - Gauged	-	-
		SLTBUTSCO2424G	24"x24"	Field Tile - Gauged	-	-
Trim		SLTBUTSCOFLAG	180-200 Sq. Ft. per Pallet	Flagstone - Natural	-	-
		SLTBUTSCOHALFRD	3/4"x12"	Half Round Molding - Honed	-	-
		SLTBUTSCOCHAIR	2"x12"	Chair Rail Molding - Honed	-	-
Mosaic		SLTBUTSCOLNR	11 3/8"x12 1/4" Sheet	Skyline Linear Mosaic - Tumbled	-	-
		SLTBUTSC00202MT	12"x12" Sheet	2"x2" Mosaic Tumbled - Tumbled	-	-

## **APPLICATIONS**

	Floors (Textured Only)	Walls	Countertops	Shower Floors (Textured & Small Mosaics Only)	Shower Walls	Pools/Spas
Residential	• †	•	•	• †	•	
Light Commercial	• †	•	•	• †	•	
Commercial	• †	•	•	• †	•	

Shade Variation



## LEGEND

Product rated for Interior & Exterior use

Product rated for Interior use only

† May be suitable for Exterior Floors

 $\varnothing$  Applications & ANSI Technical Specifications do not apply

\* Special Order only

Slate has a natural cleft rather than a smooth surface and an array of colors/shading. The foliated layers on slate tend to naturally and temporarily flake post installation as the stone settles, sometimes exposing different colors and textures. Exposure of slate to moisture, water, acid, bleach, or iron may result in oxidizing, rusting, staining or discoloration over time.

Images and product samples are representative of a product's potential characteristics. There is no guarantee that the sample product or images will 100% match the product received. Field, mosaic, and trim tile may not be an exact match. Tiles are subject to variations in color, shade, size, surface texture and finish. Prior to installation, installer must blend tiles from several different boxes to achieve an even distribution of color range. Installer must conduct a dry mock layout under proper lighting conditions prior to installation. It is the consumer's responsibility to inspect the product prior to installation to ne sure satisfaction. Once installed, the product is deemed accepted. Check Manufacturer's specifications as some Mosaic tiles may not be appropriate for wet applications. Reference the most current TCNA Handbook, ANSI, Manufacturer's specifications, and Bedrosians Care & Maintenance guide for installation, outdoor use, care and maintenance information. Improper installation, applications, acrea and maintenance voids warranty. We reserve the right to make changes to product specifications at any time without notice. Please visit www.bedrosians.com for current product information.

MKTTERSLTBUT REV. 1/2018



<sup>†</sup> The TCNA does not rate products for exterior floors. Project specifier must determine product suitability for exterior floor applications by evaluating specific project conditions, type of use, traffic, drainage, expected contaminants (such as water, oil, grease, etc.), wear, maintenance, and manufacturer's specifications and guidelines. Use caution--product may not be suitable for pool decks or ramps. No polished tiles; only textured surfaces may be suitable.