Bedrosians[®] Tile & Stone

Field Tile Sizes



Colonial White - CW STPCRACW848 - 8"x48" Rectified Field Tile - Honed



Weathered Board - WB STPCRAWB848 - 8"x48" Rectified Field Tile- Honed



Charred Bark - CB STPCRACB848 - 8"x48" Rectified Field Tile- Honed

bedrosians.com



SIZING & PACKAGING

Туре	Shape	Shape Item Code STPCRA+848		Size 8"x48"		Description Rectified Field Tile - Honed		Pcs/Ctn	Sf / Ctn 15.59
Field								6	
NSI TECH	NICAL SPECIFIC	ATIONS						Shade Varia	ation
	DCOF Acutest	PEI Rating ASTM# C1027	Frost Resistant ASTM# C1026	Scratch Resistance MOHS	Breaking Strength ASTM# C648	Water Absorption ASTM# C373	Chemical Resistance ASTM# C650	V1	/3 V4
Results	≥0.42	N/A	Unaffected	7	≥350 lbf	≤0.5%	Unaffected	V2-Sligh	it
PPLICATIO	ONS								Minimum 3/ Grout Joint
		Floors	Walls	Countertops	Shower Floors	Shower Walls	Pools/Spas		
Residential		• †	•		•†	۲		H 33% H Overlap should not exe	eed 33%
Commercial		•†	٠		•†		٠	_	
EGEND									
_	ated for Interior & Exter ons & ANSI Technical S			t rated for Interior use	-	† May be suita	ble for Exterior Floors	Use of a leveling sy installation is strongly	stem during recommended
Made in USA	Glazed Body P		Rectified Edge	Recycle	ed .	CERTIFIC RCELAIN TAS			PRODUCT CERTIFIED FOR LOW CHEMICAL EMISSIONS: JL.COM/GG JL 2818

† The TCNA does not rate products for exterior floors. Project specifier must determine product suitability for exterior floor applications by evaluating specific project conditions, type of use, traffic, drainage, expected contaminants (such as water, oil, grease, etc.), wear, maintenance, and manufacturer's specifications and guidelines. Use caution--product may not be suitable for pool decks. Not suitable for ramps. No polished tiles; only textured surfaces may be suitable.

Merchandising materials and samples are for general reference only and representative of a product's potential characteristics. Tile is subject to variation in color/shade, size, texture, and finish. Field, mosaic and trim tile may not match exactly. Blend tiles from different boxes to achieve consistent shade distribution. Installer and end user must conduct a dry mock layout under proper lighting conditions to inspect the product. Installation constitutes product acceptance. Improper installation, application, use, care and maintenance voids warranty. Reference the TCNA Handbook and ANSI for installation guidance. Please visit bedrosians.com for current product information. We reserve the right to make product changes at any time without notice.

bedrosians.com

