

Field Tile Sizes



Moon - MO

STPQUAMO412H* - 4"x12"
STPQUAMO424H* - 4"x24"
STPQUAMO624H* - 6"x24"
STPQUAMO1212H* - 12"x12"
STPQUAMO1224H* - 12"x24"



Sunset - SU

STPQUASU412H* - 4"x12"
STPQUASU424H* - 4"x24"
STPQUASU624H* - 6"x24"
STPQUASU1212H* - 12"x12"
STPQUASU1224H* - 12"x24"



Lime - LI












STPQUALI412H* - 4"x12"
STPQUALI424H* - 4"x24"
STPQUALI624H* - 6"x24"
STPQUALI1212H* - 12"x12"
STPQUALI1224H* - 12"x24"



Iron - IR


STPQUAIR412H* - 4"x12"
STPQUAIR424H* - 4"x24"
STPQUAIR624H* - 6"x24"
STPQUAIR1212H* - 12"x12"
STPQUAIR1224H* - 12"x24"

SIZING & PACKAGING

Type	Shape	Item Code	Size	Description	Pcs / Ctn	Sf / Ctn
Field		STPQUA••412H*	4"x12"	Field Tile - Honed	36	11.63
		STPQUA••424H*	4"x24"	Field Tile - Honed	18	11.69
		STPQUA••624H*	6"x24"	Field Tile - Honed	16	15.58
		STPQUA••1212H*	12"x12"	Field Tile - Honed	10	9.79
		STPQUA••1224H*	12"x24"	Field Tile - Honed	8	15.75
Trim		Ø STPQUA••16COVEIC*	1"x6"	Cove Base In Corner	4	-
		Ø STPQUA••16COVEOC*	1"x6"	Cove Base Out Corner	4	-
		STPQUA••312BN*	3"x12"	Bullnose	15	-
		Ø STPQUA••612COVE*	6"x12"	Cove Base	8	-
		STPQUA••1212STAIR*	12"x12"	Stairtread	10	-
Mosaic		Ø STPQUA••22MO*	12"x12" Sheet	2"x2" Mosaic	5	-
		Ø STPQUA••NEWMODES4*	12"x24" Sheet	New Mosaic Design 4	4	-


ANSI TECHNICAL SPECIFICATIONS

	DCOF Acutest	PEI Rating ASTM# C1027	Frost Resistant ASTM# C1026	Scratch Resistance MOHS	Breaking Strength ASTM# C648	Water Absorption ASTM# C373	Chemical Resistance ASTM# C650
Results	≥ 0.42	N/A	Unaffected	7	≥ 350 lbf	≤ 0.5%	Unaffected




APPLICATIONS

	Floors	Walls	Countertops	Shower Floors	Shower Walls	Pools/Spas
Residential	● †	■	■	● †	■	■
Light Commercial	● †	■	■	● †	■	■
Commercial	● †	■	■	● †	■	■



LEGEND

- Product rated for Interior & Exterior use
- Product rated for Interior use only
- † May be suitable for Exterior Floors
- Ø Applications & ANSI Technical Specifications do not apply
- * Special Order only



† The TCNA does not rate products for exterior floors. Project specifier must determine product suitability for exterior floor applications by evaluating specific project conditions, type of use, traffic, drainage, expected contaminants (such as water, oil, grease, etc.), wear, maintenance, and manufacturer's specifications and guidelines. Use caution--product may not be suitable for pool decks. Not suitable for ramps. No polished tiles; only textured surfaces may be suitable.

Images and product samples are representative of a product's potential characteristics. There is no guarantee that the sample product or images will 100% match the product received. Field, mosaic, and trim tile may not be an exact match. Tiles are subject to variations in color, shade, sizing, surface texture and finish. Installer must conduct a dry mock layout under proper lighting conditions prior to installation. It is the consumer's responsibility to inspect the product prior to installation to ensure satisfaction. Once installed, the product is deemed accepted. Check Manufacturer's specifications as some Mosaic tiles may not be appropriate for wet applications. Reference the most current TCNA Handbook, ANSI, Manufacturer's specifications, and Bedrosians Care & Maintenance guide for installation, outdoor use, care and maintenance information. Improper installation, application, use, care and maintenance voids warranty. We reserve the right to make changes to product specifications at any time without notice. Please visit bedrosians.com for current product information.

Bedrosians.com

MKTTERSTPQUA
REV. 5/2017