



Classico - C

- TCRCM36C - 12"x24" Matte
- TCRCM36CP - 12"x24" Polished
- TCRCM60C - 24"x24" Matte
- TCRCM60CP - 24"x24" Polished



Classico - C

- TCRCM15CM
- 1 1/2"x1 1/2" Mosaic - Matte/Polished
- (10"x12" Sheet)



Classico - C

- TCRCM60DC - 24"x24" Deco A - Matte



Classico - C


- TCRCM36D2C - 12"x24" Deco B - Matte

SIZING & PACKAGING

Type	Shape	Item Code	Size	Description	Pcs / Ctn	Sf / Ctn
Field		TCRCCEM36•	12"x24"	Field Tile - Matte	9	18.00
		∅ TCRCEM36•P	12"x24"	Field Tile - Polished	9	18.00
		TCRCCEM60•	24"x24"	Field Tile - Matte	4	16.00
Deco		∅ TCRCEM60•P	24"x24"	Field Tile - Polished	4	16.00
		TCRCCEM36D2•	12"x24"	Deco B - Matte	9	18.00
Trim		TCRCCEM60D•	24"x24"	Deco A - Matte	4	16.00
		TCRCCEM324•	3"x24"	Surface Bullnose - Matte	26	-
Mosaic		∅ TCRCEM324•P	3"x24"	Surface Bullnose - Polished	26	-
		∅ TCRCEM15•M	10"x12" Sheet	1 1/2"x1 1/2" Mosaic - Matte/Polished	11	-


ANSI TECHNICAL SPECIFICATIONS

	DCOF Acutest	PEI Rating ASTM# C1027	Frost Resistant ASTM# C1026	Scratch Resistance MOHS	Breaking Strength ASTM# C648	Water Absorption ASTM# C373	Chemical Resistance ASTM# C650
Results	N/A	3	Unaffected	7	≥ 500 lbf	≤ 0.5%	Unaffected




APPLICATIONS

	Floors	Walls	Countertops	Shower Floors	Shower Walls	Pools/Spas
Residential	•	◻	◻		◻	
Light Commercial	•	◻	◻		◻	
Commercial		◻	◻		◻	



LEGEND

- ◻ Product rated for Interior & Exterior use
- Product rated for Interior use only
- † May be suitable for Exterior Floors
- ∅ Applications & ANSI Technical Specifications do not apply
- * Special Order only



Use of a leveling system during installation is strongly recommended

For installation of all polished, polished glazed, and honed porcelain/ceramic tiles, use a grout release prior to grouting and a grout color that matches the predominant color of the tile. Refer to grout manufacturer's specifications to ensure use of proper grout. Refer to tile manufacturer's specifications to determine if the tile is appropriate for commercial applications. Tiles with a polished finish are not appropriate for wet or exterior floor applications. Do not use acidic cleaners.

Images and product samples are representative of a product's potential characteristics. There is no guarantee that the sample product or images will 100% match the product received. Field, mosaic, and trim tile may not be an exact match. Tiles are subject to variations in color, shade, sizing, surface texture and finish. Installer must conduct a dry mock layout under proper lighting conditions prior to installation. It is the consumer's responsibility to inspect the product prior to installation to ensure satisfaction. Once installed, the product is deemed accepted. Check Manufacturer's specifications as some Mosaic tiles may not be appropriate for wet applications. Reference the most current TCNA Handbook, ANSI, Manufacturer's specifications, and Bedrosians Care & Maintenance guide for installation, outdoor use, care and maintenance information. Improper installation, application, use, care and maintenance voids warranty. We reserve the right to make changes to product specifications at any time without notice. Please visit bedrosians.com for current product information.

