

Field Tile Sizes



Beige - B
TCRCLI36B - 12"x24" Matte
TCRCLI60B - 24"x24" Matte
TCRCLI6120B - 24"x48" Matte



Silver - S
TCRCLI36S - 12"x24" Matte
TCRCLI60S - 24"x24" Matte
TCRCLI6120S - 24"x48" Matte
TCRCLI6120SP - 24"x48" Polished



Nero - N
TCRCLI36N - 12"x24" Matte
TCRCLI60N - 24"x24" Matte
TCRCLI6120N - 24"x48" Matte

2"x2" Hexagon Mosaic - Matte (12"x12" Sheet)



Beige - B
TCRCLI221HEXB



Silver - S
TCRCLI221HEXS



Nero - N
TCRCLI221HEXN



Photo Features 24"x24" Field Tile - Matte in Beige.



Clive

Glazed Porcelain

Photo Features 24"x24" Field Tile - Matte In Beige.


SIZING & PACKAGING

Type	Shape	Item Code	Size	Description	Pcs / Ctn	Sf / Ctn
Field		TCRCLI36*	12"x24"	Field Tile - Matte	9	18.00
		TCRCLI60*	24"x24"	Field Tile - Matte	4	16.00
		TCRCLI6120*	24"x48"	Field Tile - Matte	2	16.00
		∅ TCRCLI6120SP	24"x48"	Field Tile - Polished (Silver Only)	2	16.00
Trim		TCRCLIS324*	3"x24"	Surface Bullnose - Matte	26	-
		∅ TCRCLIS324SP	3"x24"	Surface Bullnose - Polished (Silver Only)	26	-
Mosaic		∅ TCRCLI221HEX*	12"x12" Sheet	2"x2" Hexagon Mosaic - Matte	11	-

ANSI TECHNICAL SPECIFICATIONS


	DCOF Acutest	PEI Rating ASTM# C1027	Frost Resistant ASTM# C1026	Scratch Resistance MOHS	Breaking Strength ASTM# C648	Water Absorption ASTM# C373	Chemical Resistance ASTM# C650
Results	N/A	4	Unaffected	7	≥500 lbf	≤0.5%	Unaffected

Shade Variation




APPLICATIONS

	Floors	Walls	Countertops	Shower Floors	Shower Walls	Pools/Spas
Residential	●	◻	◻	●	◻	◻
Light Commercial	●	◻	◻	●	◻	◻
Commercial		◻	◻		◻	◻



LEGEND

- ◻ Product rated for Interior & Exterior use
- Product rated for Interior use only
- † May be suitable for Exterior Floors
- ∅ Applications & ANSI Technical Specifications do not apply
- * Special Order only



Use of a leveling system during installation is strongly recommended

Merchandising materials and samples are for general reference only and representative of a product's potential characteristics. Tile is subject to variation in color/shade, size, texture, and finish. Field, mosaic and trim tile may not match exactly. Blend tiles from different boxes to achieve consistent shade distribution. Installer and end user must conduct a dry mock layout under proper lighting conditions to inspect the product. Installation constitutes product acceptance. Improper installation, application, use, care and maintenance voids warranty. Reference the TCNA Handbook and ANSI for installation guidance. Please visit bedrosians.com for current product information. We reserve the right to make product changes at any time without notice.

