

Field Tile Size



Carmel - C TCREDD50C - 20"x20" Matte



Rosso - R TCREDD50R - 20"x20" Matte


Coordinating Products



Kismet DECKISUTORHOB Utopia - UTO Rhomboid Mosaic Blend - Matte (11"x11 3/4" Sheet)



Hemisphere DECHEMSP-KS Kona Sands - KS Sliced Pebble Mosaic - Polished (12"x12" Sheet)



360 DEC360SHA34M Shale - SHA 3/4" Penny Rounds Mosaic - Matte (12"x12" Sheet)

Bedrosians.com

SIZING & PACKAGING

Туре	Shape	Item Code	Size	Description	Pcs / Ctn	Sf / Ctn
Field		TCREDD50•	20"x20"	Field Tile - Matte	6	16.66
Trim		TCREDDS320•	3"x20"	Surface Bullnose - Matte	32	-

ANSI TECHNICAL SPECIFICATIONS

	DCOF Acutest	PEI Rating ASTM# C1027	Frost Resistant ASTM# C1026	Scratch Resistance MOHS	Breaking Strength ASTM# C648	Water Absorption ASTM# C373	Chemical Resistance ASTM# C650
Results	N/A	5	Unaffected	7	\geq 400 lbf	≤ 0.5%	Unaffected

APPLICATIONS

	Floors	Walls	Countertops	Shower Floors	Shower Walls	Pools/Spas
Residential	٠	•	٠		۲	
Light Commercial	٠	•	٠		٠	
Commercial			۲			

LEGEND

Product rated for Interior & Exterior use Product rated for Interior use only † May be suitable for Exterior Floors $\ensuremath{\varnothing}$ Applications & ANSI Technical Specifications do not apply * Special Order only

6



33% - Overlap should not exceed 33%

Shade Variation

V3-Moderate

Minimum 3/16" Grout Joint

Use of a leveling system during installation is strongly recommended

Technical specifications do not apply to Coordinating Products.

Images and product samples are representative of a product's potential characteristics. There is no guarantee that the sample product or images will 100% match the product received. Field, mosaic, and trim tile may not be an exact match. Tiles are subject to variations in color, shade, sizing, surface texture and finish. Installer must conduct a dry mock layout under proper lighting conditions prior to installation. It is the consumer's responsibility to inspect the product prior to installation to ensure satisfaction. Once installed, the product is deemed accepted. Check Manufacturer's specifications as some Mosaic tiles may not be appropriate for wet applications. Reference the most current TCNA Handbook, ANSI, Manufacturer's specifications, and Bedrosians Care & Maintenance guide for installation, outdoor use, care and maintenance information. Improper installation, application, use, care and maintenance voids warranty. We reserve the right to make changes to product specifications at any time without notice. Please visit bedrosians.com for current product information.



