



# Infinity

Glazed Porcelain





# Infinity Glazed Porcelain



## Cosmic



TCRINF36C - 12" x 24"  
TCRINF36CL - 12" x 24" Lappato

## Night



TCRINF36N - 12" x 24"  
TCRINF36NL - 12" x 24" Lappato

## Luna



TCRINF36L - 12" x 24"  
TCRINF36LL - 12" x 24" Lappato

## Asteroid



TCRINF36A - 12" x 24"  
TCRINF36AL - 12" x 24" Lappato

## Kona



TCRINF36K - 12" x 24"  
TCRINF36KL - 12" x 24" Lappato

## Coordinating Listellos



Cosmic  
TCRINF36CL  
Listello  
6" x 16" sheet



Night  
TCRINF36NL  
Listello  
6" x 16" sheet



Luna  
TCRINF36LL  
Listello  
6" x 16" sheet



Asteroid  
TCRINF36AL  
Listello  
6" x 16" sheet



Kona  
TCRINF36KL  
Listello  
6" x 16" sheet

## Sizes



Tile Thickness: 3/8"

## Packaging

Type	Size	Item Code	Pcs / Ctn	Sf / Ctn	Ctn / Plt	Sf / Plt
Field Tile	12"x24"	TCRINF36•	9	18.00	40	720.00
Field Tile	12"x24" Lappato	TCRINF36•L	9	18.00	40	720.00
Bullnose	3"x24"	TCRINF36B•				
Bullnose	3"x24" Lappato	TCRINF36B•L				
1 1/2"x1 1/2" Mosaic	10"x11 3/4" Sheet	TCRINF15•M				
Listello	6"x16" Sheet	TCRINF36•L				



## Applications

	Floors	Walls	Countertops	Showers	Floors	Showers	Walls	Pools
Residential	●	●	●				●	
Light Commercial	●	●	●				●	
Commercial		●	●				●	

Legend:  Product rated for interior & exterior use    ● Interior use only

## Technical Specifications

Technical Specifications	Results	ASTM#
Water Absorption	≤ 0.50%	C373
PEI Rating	4	C1027
Scratch Resistance	7	MOHS
Frost Resistant	N/A	C1026
DCOF Acutest	N/A	AcuTest
Breaking Strength	N/A	C648
Chemical Resistant	N/A	C650



The maximum allowable installation offset is 33%. Minimum grout joint must be 3/16 inch. Please refer to the most current TCNA Handbook. Manufacturer strongly recommends use of a leveling system during installation.

For installation of all polished porcelain, polished glazed porcelain, and all honed porcelain tiles, Manufacturer requires use of a grout release or sealer prior to grouting. Manufacturer also requires use of a grout color that matches the predominant color of the tile. Do not use acidic cleaners on polished or polished glazed porcelain tiles. Do not install in pools, spas/hot tubs, and/or submerged applications.

Images and product samples are representative of a product's potential characteristics. There is no guarantee the sample product or images will 100% match the product received. Field and trim tile may not be an exact match. We reserve the right to make changes to product specifications at any time without notice. Tiles are subject to variations in color, shade, sizing, surface texture and finish. Prior to installation, installer must blend tiles from several different boxes to achieve an even distribution of color range. Installer must conduct a dry mock layout under proper lighting conditions prior to installation. It is the consumer's responsibility to inspect the product prior to installation to ensure satisfaction. Once installed, the product is deemed accepted. Reference the most current TCNA Handbook, ANSI, manufacturer's specifications, and Bedrosians Care & Maintenance guide for installation, outdoor use, care and maintenance information. Improper installation, application, and use voids warranty.