



**Novona - N**  
TCRPHN36N - 12"x24" Matte  
TCRPHN36NP - 12"x24" Polished  
TCRPHN602CMN - 24"x24" 2cm - Matte  
TCRPHN6120N - 24"x48" Matte  
TCRPHN6120NP - 24"x48" Polished



**Novona - N**  
TCRPHN15NM  
1 1/2"x1 1/2" Mosaic - Matte/Polished Blend  
(10"x12" Sheet)



**Silver - S**  
TCRPHN36S - 12"x24" Matte  
TCRPHN36SP - 12"x24" Polished  
TCRPHN602CMS - 24"x24" 2cm - Matte  
TCRPHN6120S - 24"x48" Matte  
TCRPHN6120SP - 24"x48" Polished



**Silver - S**  
TCRPHN15SM  
1 1/2"x1 1/2" Mosaic - Matte/Polished Blend  
(10"x12" Sheet)




## SIZING & PACKAGING

Type	Shape	Item Code	Size	Description	Pcs / Ctn	Sf / Ctn
Field		TCRPHN36•	12"x24"	Field Tile - Matte	9	18.00
		∅ TCRPHN36•P	12"x24"	Field Tile - Polished	9	18.00
		TCRPHN602CM•	24"x24"	2cm Field Tile - Matte	2	8.00
		TCRPHN6120•	24"x48"	Field Tile - Matte	2	16.00
Trim		∅ TCRPHN6120•P	24"x48"	Field Tile - Polished	2	16.00
		TCRPHNS324•	3"x24"	Surface Bullnose - Matte	-	-
Mosaic		∅ TCRPHNS324•P	3"x24"	Surface Bullnose - Polished	-	-
		∅ TCRPHN15•M	10"x12" Sheet	11/2"x12" Mosaic - Matte/Polished Blend	12	-


## ANSI TECHNICAL SPECIFICATIONS

	DCOF Acutest	PEI Rating ASTM# C1027	Frost Resistant ASTM# C1026	Scratch Resistance MOHS	Breaking Strength ASTM# C648	Water Absorption ASTM# C373	Chemical Resistance ASTM# C650
Results	N/A	4	Unaffected	7	≥ 500 lbf	≤ 0.5%	Unaffected



## ANSI TECHNICAL SPECIFICATIONS - 2cm Field Tile

	DCOF Acutest	PEI Rating ASTM# C1027	Frost Resistant ASTM# C1026	Scratch Resistance MOHS	Breaking Strength ASTM# C648	Water Absorption ASTM# C373	Chemical Resistance ASTM# C650
Results	≥ 0.42	4	Unaffected	7	≥ 500 lbf	≤ 0.5%	Unaffected




## APPLICATIONS

	Floors	Walls	Countertops	Shower Floors	Shower Walls	Pools/Spas
Residential	●	◻	◻		◻	
Light Commercial		◻	◻		◻	

## APPLICATIONS - 2cm Field Tile

	Floors	Walls	Countertops	Shower Floors	Shower Walls	Pools/Spas
Residential	◻	◻	◻	◻	◻	◻
Light Commercial	◻	◻	◻	◻	◻	◻



## LEGEND

- ◻ Product rated for Interior & Exterior use
- Product rated for Interior use only
- † May be suitable for Exterior Floors
- ∅ Applications & ANSI Technical Specifications do not apply
- \* Special Order only



For installation of all polished, polished glazed, and honed porcelain tiles, use a grout release prior to grouting and a grout color that matches the predominant color of the tile. Refer to grout manufacturer's specifications to ensure use of proper grout. Refer to tile manufacturer's specifications to determine if the tile is appropriate for commercial applications. Tiles with a polished finish are not appropriate for wet, exterior, or countertop applications. Do not use acidic cleaners.

Merchandising materials and samples are for general reference only and representative of a product's potential characteristics. Tile is subject to variation in color/shade, size, texture, and finish. Field, mosaic and trim tile may not match exactly. Blend tiles from different boxes to achieve consistent shade distribution. Installer and end user must conduct a dry mock layout under proper lighting conditions to inspect the product. Installation constitutes product acceptance. Improper installation, application, use, care and maintenance voids warranty. Reference the TCNA Handbook and ANSI for installation guidance. Please visit [bedrosians.com](http://bedrosians.com) for current product information. We reserve the right to make product changes at any time without notice.

