

Field Tile Sizes



White Coral - W
TCRREE60W - 24"x24" - Matte
TCRREE602CMW - 24"x24" 2cm - Matte



Pearl Coral - P
TCRREE60P - 24"x24" - Matte
TCRREE602CMP - 24"x24" 2cm - Matte



Beige Coral - B
TCRREE60B - 24"x24" - Matte
TCRREE602CMB - 24"x24" 2cm - Matte



Gray Coral - G
TCRREE60G - 24"x24" - Matte
TCRREE602CMG - 24"x24" 2cm - Matte



Ebony Coral - E
TCRREE60E - 24"x24" - Matte
TCRREE602CME - 24"x24" 2cm - Matte







Reefstone

Glazed Porcelain

Photo Features 24"x24" Field Tile - Matte in Pearl Coral.


SIZING & PACKAGING

Type	Shape	Item Code	Size	Description	Pcs / Ctn	Sf / Ctn
Field		TCRREE60*	24"x24"	Field Tile - Matte	4	16.00
		TCRREE602CM*	24"x24"	2cm Field Tile - Matte	2	8.00

ANSI TECHNICAL SPECIFICATIONS

	DCOF Acutest	PEI Rating ASTM# C1027	Frost Resistant ASTM# C1026	Scratch Resistance MOHS	Breaking Strength ASTM# C648	Water Absorption ASTM# C373	Chemical Resistance ASTM# C650
Results	≥ 0.42	4	Unaffected	7	≥ 500 lbf	≤ 0.5%	Unaffected

Shade Variation




APPLICATIONS - 24"x24" Field Tile

	Floors	Walls	Countertops	Shower Floors	Shower Walls	Pools/Spas
Residential	•	◻	◻	•	◻	◻
Light Commercial	•	◻	◻	•	◻	◻


APPLICATIONS - 24"x24" 2cm Field Tile

	Floors	Walls	Countertops	Shower Floors	Shower Walls	Pools/Spas
Residential	◻	◻	◻	◻	◻	◻
Light Commercial	◻	◻	◻	◻	◻	◻



LEGEND

- ◻ Product rated for Interior & Exterior use
- Product rated for Interior use only
- † May be suitable for Exterior Floors
- ∅ Applications & ANSI Technical Specifications do not apply
- * Special Order only



Merchandising materials and samples are for general reference only and representative of a product's potential characteristics. Tile is subject to variation in color/shade, size, texture, and finish. Field, mosaic and trim tile may not match exactly. Blend tiles from different boxes to achieve consistent shade distribution. Installer and end user must conduct a dry mock layout under proper lighting conditions to inspect the product. Installation constitutes product acceptance. Improper installation, application, use, care and maintenance voids warranty. Reference the TCNA Handbook and ANSI for installation guidance. Please visit bedrosians.com for current product information. We reserve the right to make product changes at any time without notice.

