

Field Tile Sizes



Almond - A
TCRROM30AT - 12"x12" Matte
TCRROM36AT - 12"x24" Matte
TCRROM50AT - 20"x20" Matte
TCRROM60AT - 24"x24" Matte



Beige - B
TCRROM30BT - 12"x12" Matte
TCRROM36BT - 12"x24" Matte
TCRROM50BT - 20"x20" Matte
TCRROM60BT - 24"x24" Matte



Camel - C
TCRROM30CT - 12"x12" Matte
TCRROM36CT - 12"x24" Matte
TCRROM50CT - 20"x20" Matte
TCRROM60CT - 24"x24" Matte



Noce - N
TCRROM30NT - 12"x12" Matte
TCRROM36NT - 12"x24" Matte
TCRROM50NT - 20"x20" Matte
TCRROM60NT - 24"x24" Matte

2"x2" Mosaic - Matte (13"x13" Sheet)



Almond - A
TCRRROM22AT



Beige - B
TCRRROM22BT



Camel - C
TCRRROM22CT



Noce - N
TCRRROM22NT


SIZING & PACKAGING

Type	Shape	Item Code	Size	Description	Pcs / Ctn	Sf / Ctn
Field		TCRRROM30•T	12"x12"	Field Tile - Matte	13	13.00
		TCRRROM36•T	12"x24"	Field Tile - Matte	9	18.00
		TCRRROM50•T	20"x20"	Field Tile - Matte	6	16.66
		TCRRROM60•T	24"x24"	Field Tile - Matte	4	16.00
Trim		∅ TCRROMAC•	1"x1"	Beak - Matte	-	-
		∅ TCRROMA112•	1"x12"	Quarter Round - Matte	80	-
		TCRRROMS320•T	3"x20"	Surface Bullnose - Matte	32	-
Mosaic		TCRRROM22•T	13"x13" Sheet	2"x2" Mosaic - Matte	11	-

ANSI TECHNICAL SPECIFICATIONS


	DCOF Acutest	PEI Rating ASTM# C1027	Frost Resistant ASTM# C1026	Scratch Resistance MOHS	Breaking Strength ASTM# C648	Water Absorption ASTM# C373	Chemical Resistance ASTM# C650
Results	≥ 0.42	5	Unaffected	7	≥ 400 lbf	≤ 0.5%	Unaffected

Shade Variation



APPLICATIONS

	Floors	Walls	Countertops	Shower Floors	Shower Walls	Pools/Spas
Residential	•	◻	◻	•	◻	
Light Commercial	•	◻	◻	•	◻	
Commercial	•	◻	◻	•	◻	



LEGEND

- ◻ Product rated for Interior & Exterior use
- Product rated for Interior use only
- † May be suitable for Exterior Floors
- ∅ Applications & ANSI Technical Specifications do not apply
- * Special Order only




Glazed Porcelain



Rectified Edge



Ink Jet



Use of a leveling system during installation is strongly recommended

For installation of all polished, polished glazed, and honed porcelain tiles, use a grout release prior to grouting and a grout color that matches the predominant color of the tile. Refer to grout manufacturer's specifications to ensure use of proper grout. Refer to tile manufacturer's specifications to determine if the tile is appropriate for commercial applications. Tiles with a polished finish are not appropriate for wet, exterior, or countertop applications. Do not use acidic cleaners.

Images and product samples are representative of a product's potential characteristics. There is no guarantee that the sample product or images will 100% match the product received. Field and trim tile may not be an exact match. We reserve the right to make changes to product specifications at any time without notice. Tiles are subject to variations in color, shade, sizing, surface texture and finish. Prior to installation, installer must blend tiles from several different boxes to achieve an even distribution of color range. Installer must conduct a dry mock layout under proper lighting conditions prior to installation. It is the consumer's responsibility to inspect the product prior to installation to ensure satisfaction. Once installed, the product is deemed accepted. Reference the most current TCNA Handbook, ANSI, manufacturer's specifications, and the Bedrosians Care & Maintenance guide for installation, outdoor use, care and maintenance information. Improper installation, application, and/or use voids warranty. Please visit www.bedrosians.com for current product information.

