

Field Tile Sizes



Light Gray - LG
TCRTER25LG - 10"x10" Matte
TCRTER50LG - 20"x20" Matte



Medium Gray - MG
TCRTER25MG - 10"x10" Matte
TCRTER50MG - 20"x20" Matte



Dark Gray - DG
TCRTER25DG - 10"x10" Matte
TCRTER50DG - 20"x20" Matte

2"x2" Hexagon Mosaic - Matte (12"x12" Sheet)



Light Gray - LG
TCRTER221HEXLG



Medium Gray - MG
TCRTER221HEXMG



Dark Gray - DG
TCRTER221HEXDG

20"x20" Deco - Matte



Light Gray, Medium Gray & Dark Gray
TCRTERDEC150



Terrazzo

Glazed Porcelain

Photo Features 20"x20" Field Tile - Matte in Dark Gray

SIZING & PACKAGING

Type	Shape	Item Code	Size	Description	Pcs / Ctn	Sf / Ctn
Field		TCRTER25**	10"x10"	Field Tile - Matte	16	11.00
		TCRTER50**	20"x20"	Field Tile - Matte	6	16.66
Deco		TCRTERDEC150	20"x20"	Deco with All Three Colors - Matte	6	16.66
Trim		TCRTERS320**	3"x20"	Surface Bullnose - Matte	32	-
Mosaic		∅ TCRTER221HEX**	12"x12" Sheet	2"x2" Hexagon Mosaic - Matte	11	-

ANSI TECHNICAL SPECIFICATIONS


	DCOF Acutest	PEI Rating ASTM# C1027	Frost Resistant ASTM# C1026	Scratch Resistance MOHS	Breaking Strength ASTM# C648	Water Absorption ASTM# C373	Chemical Resistance ASTM# C650
Results	≥0.42	4	Unaffected	7	≥500 lbf	≤0.5%	Unaffected

Shade Variation




APPLICATIONS

	Floors	Walls	Countertops	Shower Floors	Shower Walls	Pools/Spas
Residential	●	◻	◻	●	◻	◻
Light Commercial	●	◻	◻	●	◻	◻
Commercial	●	◻	◻	●	◻	◻



LEGEND

- ◻ Product rated for Interior & Exterior use
- Product rated for Interior use only
- † May be suitable for Exterior Floors
- ∅ Applications & ANSI Technical Specifications do not apply
- * Special Order only



Use of a leveling system during installation is strongly recommended

Merchandising materials and samples are for general reference only and representative of a product's potential characteristics. Tile is subject to variation in color/shade, size, texture, and finish. Field, mosaic and trim tile may not match exactly. Blend tiles from different boxes to achieve consistent shade distribution. Installer and end user must conduct a dry mock layout under proper lighting conditions to inspect the product. Installation constitutes product acceptance. Improper installation, application, use, care and maintenance voids warranty. Reference the TCNA Handbook and ANSI for installation guidance. Please visit bedrosians.com for current product information. We reserve the right to make product changes at any time without notice.

