

Field Tile Sizes



White - W

TCRTRO36W - 12"x24" Matte
TCRTRO60W - 24"x24" Matte
TCRTRO6120W - 24"x48" Matte
TCRTRO6120WP - 24"x48" Polished



Beige - B

TCRTRO36B - 12"x24" Matte
TCRTRO60B - 24"x24" Matte
TCRTRO6120B - 24"x48" Matte



Silver - S

TCRTRO36S - 12"x24" Matte
TCRTRO60S - 24"x24" Matte
TCRTRO6120S - 24"x48" Matte
TCRTRO6120SP - 24"x48" Polished



Nero - N

TCRTRO36N - 12"x24" Matte
TCRTRO60N - 24"x24" Matte
TCRTRO6120N - 24"x48" Matte

2"x2" Hexagon Mosaic - Matte (12"x12" Sheet)




White - W

TCRTRO221HEXW




Beige - B

TCRTRO221HEXB



Silver - S

TCRTRO221HEXS



Nero - N

TCRTRO221HEXN



Photo Features 24"x24" Field Tile - Matte in Silver.




Photo Features 24"x24" Field Tile - Matte in Silver.

SIZING & PACKAGING

Type	Shape	Item Code	Size	Description	Pcs / Ctn	Sf / Ctn
Field		TCRTRO36•	12"x24"	Field Tile - Matte	9	18.00
		TCRTRO60•	24"x24"	Field Tile - Matte	4	16.00
		TCRTRO6120•	24"x48"	Field Tile - Matte	2	16.00
		∅ TCRTRO6120SP	24"x48"	Field Tile - Polished (Silver & White Only)	2	16.00
Trim		TCRTROS324•	3"x24"	Surface Bullnose - Matte	26	-
		∅ TCRTROS324SP	3"x24"	Surface Bullnose - Polished (Silver & White Only)	26	-
Mosaic		∅ TCRTRO221HEX•	12"x12" Sheet	2"x2" Hexagon Mosaic - Matte	11	-


ANSI TECHNICAL SPECIFICATIONS

	DCOF Acutest	PEI Rating ASTM# C1027	Frost Resistant ASTM# C1026	Scratch Resistance MOHS	Breaking Strength ASTM# C648	Water Absorption ASTM# C373	Chemical Resistance ASTM# C650
Results	N/A	4	Unaffected	7	≥500 lbf	≤0.5%	Unaffected




APPLICATIONS

	Floors	Walls	Countertops	Shower Floors	Shower Walls	Pools/Spas
Residential	•	◻	◻	•	◻	◻
Light Commercial	•	◻	◻	•	◻	◻
Commercial		◻	◻		◻	◻



LEGEND

- ◻ Product rated for Interior & Exterior use
- Product rated for Interior use only
- † May be suitable for Exterior Floors
- ∅ Applications & ANSI Technical Specifications do not apply
- * Special Order only



Merchandising materials and samples are for general reference only and representative of a product's potential characteristics. Tile is subject to variation in color/shade, size, texture, and finish. Field, mosaic and trim tile may not match exactly. Blend tiles from different boxes to achieve consistent shade distribution. Installer and end user must conduct a dry mock layout under proper lighting conditions to inspect the product. Installation constitutes product acceptance. Improper installation, application, use, care and maintenance voids warranty. Reference the TCNA Handbook and ANSI for installation guidance. Please visit bedrosians.com for current product information. We reserve the right to make product changes at any time without notice.

