


12"x24" Rectified Porcelain Field Tile - Matte




White - W
TCRUNI36W



Silver - S
TCRUNI36S



Taupe - T
TCRUNI36T



Black - B
TCRUNI36B


8"x8" Non-Rectified Hexagon Ceramic Field Tile - Matte




White - W
TCRUNI88HEXW



Silver - S
TCRUNI88HEXS




Taupe - T
TCRUNI88HEXT



Black - B
TCRUNI88HEXB


2"x2" Porcelain Mosaic - Matte (12"x12" Sheet)




White - W
TCRUNI221W



Silver - S
TCRUNI221S







Taupe - T
TCRUNI221T




Black - B
TCRUNI221B

SIZING & PACKAGING

Type	Shape	Item Code	Size	Description	Pcs / Ctn	Sf / Ctn
Field		TCRUNI88HEX*	8"x8"	Non-Rectified Hexagon Ceramic Tile - Matte	20	7.42
		TCRUNI36*	12"x24"	Rectified Porcelain Field Tile - Matte	9	18.00
Trim		TCRUNIS324*	3"x24"	Porcelain Surface Bullnose - Matte	26	-
Mosaic		TCRUNI221*	12"x12" Sheet	2"x2" Porcelain Mosaic - Matte	12	-


ANSI TECHNICAL SPECIFICATIONS - 8"x8" Hex Non-Rectified Ceramic Tile

	DCOF Acutest	PEI Rating ASTM# C1027	Frost Resistant ASTM# C1026	Scratch Resistance MOHS	Breaking Strength ASTM# C648	Water Absorption ASTM# C373	Chemical Resistance ASTM# C650
Results	N/A	3	N/A	5	≥ 250 lbf	≥ 1.0% Ceramic	Unaffected



ANSI TECHNICAL SPECIFICATIONS - 12"x24" Rectified Porcelain Field Tile

	DCOF Acutest	PEI Rating ASTM# C1027	Frost Resistant ASTM# C1026	Scratch Resistance MOHS	Breaking Strength ASTM# C648	Water Absorption ASTM# C373	Chemical Resistance ASTM# C650
Results	≥ 0.42	4	Unaffected	7	≥ 550 lbf	≤ 0.5%	Unaffected




APPLICATIONS - Ceramic

	Floors	Walls	Countertops	Shower Floors	Shower Walls	Pools/Spas
Residential	●	●	●		●	
Commercial		●			●	


APPLICATIONS - Porcelain

	Floors	Walls	Countertops	Shower Floors	Shower Walls	Pools/Spas
Residential	●	◻	◻	●	◻	
Commercial	●	◻	◻	●	◻	



LEGEND

- ◻ Product rated for Interior & Exterior use
- Product rated for Interior use only
- † May be suitable for Exterior Floors
- ⊗ Applications & ANSI Technical Specifications do not apply
- * Special Order only



Merchandising materials and samples are for general reference only and representative of a product's potential characteristics. Tile is subject to variation in color/shade, size, texture, and finish. Field, mosaic and trim tile may not match exactly. Blend tiles from different boxes to achieve consistent shade distribution. Installer and end user must conduct a dry mock layout under proper lighting conditions to inspect the product. Installation constitutes product acceptance. Improper installation, application, use, care and maintenance voids warranty. Reference the TCNA Handbook and ANSI for installation guidance. Please visit bedrosians.com for current product information. We reserve the right to make product changes at any time without notice.

