



## Almond



TCRVER30AT - 12" x 12"  
TCRVER50AT - 20" x 20"



TCRVER22AT  
2" x 2" Mosaic  
Mesh-mounted  
on a 12" x 12" sheet

## Silver



TCRVER30ST - 12" x 12"  
TCRVER50ST - 20" x 20"



TCRVER22ST  
2" x 2" Mosaic  
Mesh-mounted  
on a 12" x 12" sheet

## Olive




TCRVER30OT - 12" x 12"  
TCRVER50OT - 20" x 20"



TCRVER22OT  
2" x 2" Mosaic  
Mesh-mounted  
on a 12" x 12" sheet

## Sizes




Tile Thickness: 3/8"

## Mosaics

Shape	Type	Sheet Size
	2"x2" Mosaic (Mesh-mounted on a sheet)	13"x13"

## Trim

Shape	Type	Size
	Bullnose	3"x20"
	Quarter Round Quarter Round	1"x6 1/2" 1"x12"
	Beak	1"x1"



Do not install in pools, spas/hot tubs, and/or submerged applications.

The maximum allowable installation offset is 33%. Minimum grout joint must be 3/16 inch. Please refer to the most current TCNA Handbook. Manufacturer strongly recommends use of a leveling system during installation.

Images and product samples are representative of a product's potential characteristics. There is no guarantee the sample product or images will 100% match the product received. Field and trim tile may not be an exact match. We reserve the right to make changes to product specifications at any time without notice. Tiles are subject to variations in color, shade, sizing, surface texture and finish. Prior to installation, installer must blend tiles from several different boxes to achieve an even distribution of color range. Installer must conduct a dry mock layout under proper lighting conditions prior to installation. It is the consumer's responsibility to inspect the product prior to installation to ensure satisfaction. Once installed, the product is deemed accepted. Reference the most current TCNA Handbook, ANSI, manufacturer's specifications, and Bedrosians Care & Maintenance guide for installation, outdoor use, care and maintenance information. Improper installation, application, and use voids warranty.

## Packaging

Type	Size	Item Code	Pcs / Ctn	Sf / Ctn	Ctn / Plt
Field Tile	12"x12"	TCRVER30•T	13	13.00	46
Field Tile	20"x20"	TCRVER50•T	6	16.66	32
Bullnose	3"x20"	TCRVERS320•T			
Quarter Round	1"x12"	TCRVERA112•T			
Beak	1"x1"	TCRVERAC•T			
2"x2" Mosaic	12"x12" Sheet	TCRVER22•T			

## Applications

	Floors	Walls	Countertops	Showers Floors	Showers Walls	Pools
Residential	●	●	●	●	●	
Light Commercial	●	●	●	●	●	
Commercial		●	●		●	

Legend:  Product rated for interior & exterior use    ● Interior use only

Technical Specifications	Results	ASTM#
Water Absorption	≤ 0.50%	C373
PEI Rating	5	C1027
Scratch Resistance	7	MOHS
Frost Resistant	N/A	C1026
DCOF Acutest	N/A	AcuTest
Breaking Strength	≥ 250 lbs	C648
Chemical Resistant	Unaffected	C650

