

Field Tile Sizes



**Silver - S**  
TCRYOS36S - 12"x24" Matte  
TCRYOS36SP - 12"x24" Polished  
TCRYOS50S - 20"x20" Matte  
TCRYOS60S - 24"x24" Matte  
TCRYOS60SP - 24"x24" Polished



**Almond - A**  
TCRYOS36A - 12"x24" Matte  
TCRYOS36AP - 12"x24" Polished  
TCRYOS50A - 20"x20" Matte  
TCRYOS60A - 24"x24" Matte  
TCRYOS60AP - 24"x24" Polished



**Beige - B**  
TCRYOS36B - 12"x24" Matte  
TCRYOS36BP - 12"x24" Polished  
TCRYOS60B - 24"x24" Matte  
TCRYOS60BP - 24"x24" Polished

2"x6" Chevron Mosaic - Polished (9 1/2"x11 3/4" Sheet)



**Silver - S**  
TCRYOSCHVSP



**Almond - A**  
TCRYOSCHVAP



**Beige - B**  
TCRYOSCHVBP

1 1/2"x1 1/2" Mosaic Blend - Matte/Polished (10"x11 3/4" Sheet)



**Silver - S**  
TCRYOS15SM



**Almond - A**  
TCRYOS15AM



**Beige - B**  
TCRYOS15BM

# Yosemite

## Glazed Porcelain

Photo Features 12"x24" Field Tile - Matte in Silver & Chevron Mosaic - Polished in Silver.


### SIZING & PACKAGING

Type	Shape	Item Code	Size	Description	Pcs / Ctn	Sf / Ctn
Field		TCRYOS36•	12"x24"	Field Tile - Matte	9	18.00
		∅ TCRYOS36•P	12"x24"	Field Tile - Polished	9	18.00
		TCRYOS50•	20"x20"	Field Tile - Matte (Available in A & S Colors Only)	6	16.66
		TCRYOS60•	24"x24"	Field Tile - Matte	4	16.00
		∅ TCRYOS60•P	24"x24"	Field Tile - Polished	4	16.00
Trim		TCRYOSS324•	3"x24"	Surface Bullnose - Matte	26	-
		∅ TCRYOSS324•P	3"x24"	Surface Bullnose - Polished	26	-
Mosaic		∅ TCRYOSCHV•P	9 1/2"x11 3/4" Sheet	2"x6" Chevron Mosaic - Polished	14	-
		∅ TCRYOS15•M	10"x11 3/4" Sheet	1 1/2"x1 1/2" Mosaic Blend - Matte/Polished	12	-

### ANSI TECHNICAL SPECIFICATIONS


	DCOF Acutest	PEI Rating ASTM# C1027	Frost Resistant ASTM# C1026	Scratch Resistance MOHS	Breaking Strength ASTM# C648	Water Absorption ASTM# C373	Chemical Resistance ASTM# C650
Results	N/A	4	Unaffected	7	≥ 550 lbf	≤ 0.5%	Unaffected

#### Shade Variation



### APPLICATIONS

	Floors	Walls	Countertops	Shower Floors	Shower Walls	Pools/Spas
Residential	●	◻	◻		◻	
Light Commercial	●	◻	◻		◻	
Commercial		◻	◻		◻	



### LEGEND

- ◻ Product rated for Interior & Exterior use
- Product rated for Interior use only
- † May be suitable for Exterior Floors
- ∅ Applications & ANSI Technical Specifications do not apply
- \* Special Order only




Glazed Porcelain



Rectified Edge



Ink Jet



Use of a leveling system during installation is strongly recommended

For installation of all polished, polished glazed, and honed porcelain tiles, use a grout release prior to grouting and a grout color that matches the predominant color of the tile. Refer to grout manufacturer's specifications to ensure use of proper grout. Refer to tile manufacturer's specifications to determine if the tile is appropriate for commercial applications. Tiles with a polished finish are not appropriate for wet, exterior, or countertop applications. Do not use acidic cleaners.

Merchandising materials and samples are for general reference only and representative of a product's potential characteristics. Tile is subject to variation in color/shade, size, texture, and finish. Field, mosaic and trim tile may not match exactly. Blend tiles from different boxes to achieve consistent shade distribution. Installer and end user must conduct a dry mock layout under proper lighting conditions to inspect the product. Installation constitutes product acceptance. Improper installation, application, use, care and maintenance voids warranty. Reference the TCNA Handbook and ANSI for installation guidance. Please visit bedrosians.com for current product information. We reserve the right to make product changes at any time without notice.

