

Available Sizes

---



TRVAYMCRM1224FHVC - 12"x24" Filled Vein-Cut - Honed  
TRVAYMCRM1224PVC - 12"x24" Filled Vein-Cut - Polished  
TRVAYMCRM1818FH - 18"x18" Filled & Honed  
TRVAYMCRM1836FHVC - 18"x36" Filled Vein-Cut - Honed  
TRVAYMCRM1836PVC - 18"x36" Filled Vein-Cut - Polished  
TRVAYMCRM2424FH - 24"x24" Filled & Honed



TRVAYMCRMSLAB2FH - 2cm Slab Filled & Honed  
TRVAYMCRMSLAB2P - 2cm Slab Filled & Polished  
TRVAYMCRMSLAB2FHVC - 2cm Slab Filled Vein-Cut - Honed  
TRVAYMCRMSLAB2PVC - 2cm Slab Filled Vein-Cut - Polished


**SIZING & PACKAGING**

Type	Shape	Item Code	Size	Description	Pcs / Ctn	Sf / Ctn
Field		TRVAYMCRM1224FHVC	12"x24"	Field Tile - Filled Vein-Cut - Honed	-	-
		TRVAYMCRM1224PVC	12"x24"	Field Tile - Filled Vein-Cut - Polished	-	-
		TRVAYMCRM1818FH	18"x18"	Field Tile - Filled & Honed	-	-
		TRVAYMCRM1836FHVC	18"x36"	Field Tile - Filled Vein-Cut - Honed	-	-
		TRVAYMCRM1836PVC	18"x36"	Field Tile - Filled Vein-Cut - Polished	-	-
		TRVAYMCRM2424FH	24"x24"	Field Tile - Filled & Honed	-	-
	Slab		TRVAYMCRMSLAB2FH	2cm	2cm Slab - Filled & Honed	-
		TRVAYMCRMSLAB2P	2cm	2cm Slab - Filled & Polished	-	-
		TRVAYMCRMSLAB2FHVC	2cm	2cm Slab - Filled Vein-Cut - Honed	-	-
		TRVAYMCRMSLAB2PVC	2cm	2cm Slab - Filled Vein-Cut - Polished	-	-

**APPLICATIONS**

	Floors (Textured Only)	Walls	Countertops	Shower Floors (Textured Only)	Shower Walls	Pools/Spas
Residential	● †	☐	☐	● †	☐	
Commercial	● †	☐	☐	● †	☐	

Shade Variation



**LEGEND**

- ☐ Product rated for Interior & Exterior use
- Product rated for Interior use only
- † May be suitable for Exterior Floors
- ∅ Applications & ANSI Technical Specifications do not apply
- \* Special Order only



† The TCNA does not rate products for exterior floors. Project specifier must determine product suitability for exterior floor applications by evaluating specific project conditions, type of use, traffic, drainage, expected contaminants (such as water, oil, grease, etc.), wear, maintenance, and manufacturer's specifications and guidelines. Use caution--product may not be suitable for pool decks. Not suitable for ramps. No polished tiles; only textured surfaces may be suitable.

Since travertine is a capillary filled stone, foot traffic or high pressure items may expose these voids. To remedy, seal the surrounding area and fill the hole with sanded or epoxy grout in a color that matches the stone. Then re-seal the stone.

Merchandising materials and samples are for general reference only and representative of a product's potential characteristics. Tile is subject to variation in color/shade, size, texture, and finish. Field, mosaic and trim tile may not match exactly. Blend tiles from different boxes to achieve consistent shade distribution. Installer and end user must conduct a dry mock layout under proper lighting conditions to inspect the product. Installation constitutes product acceptance. Improper installation, application, use, care and maintenance voids warranty. Reference the TCNA Handbook and ANSI for installation guidance. Please visit [bedrosians.com](http://bedrosians.com) for current product information. We reserve the right to make product changes at any time without notice.

