

Field Tile Sizes



Driftwood - DRI
VMXBALDRI724 - 7"x24" Non-Rectified Field Tile - Matte



Pelican - PEL
VMXBALPEL724 - 7"x24" Non-Rectified Field Tile - Matte




Dock - DOC
VMXBALDOC724 - 7"x24" Non-Rectified Field Tile - Matte

Balboa

Red Body Ceramic Tile

Photo Features 7"x24" Non-Rectified Field Tile - Matte in Dock.


SIZING & PACKAGING

Type	Shape	Item Code	Size	Description	Pcs / Ctn	Sf / Ctn
Field		VMXBAL***724	7"x24"	Non-Rectified Field Tile - Matte	15	17.61

ANSI TECHNICAL SPECIFICATIONS


	DCOF Acutest	PEI Rating ASTM# C1027	Frost Resistant ASTM# C1026	Scratch Resistance MOHS	Breaking Strength ASTM# C648	Water Absorption ASTM# C373	Chemical Resistance ASTM# C650
Results	>.62	4	N/A	N/A	>250lbf	>.7.0	Unaffected

Shade Variation




APPLICATIONS

	Floors	Walls	Countertops	Shower Floors	Shower Walls	Pools/Spas
Residential	•	•				
Commercial	•	•				



LEGEND

- Product rated for Interior & Exterior use
- Applications & ANSI Technical Specifications do not apply
- Product rated for Interior use only
- * Special Order only
- † May be suitable for Exterior Floors



Use of a leveling system during installation is strongly recommended

Merchandising materials and samples are for general reference only and representative of a product's potential characteristics. Tile is subject to variation in color/shade, size, texture, and finish. Field, mosaic and trim tile may not match exactly. Blend tiles from different boxes to achieve consistent shade distribution. Installer and end user must conduct a dry mock layout under proper lighting conditions to inspect the product. Installation constitutes product acceptance. Improper installation, application, use, care and maintenance voids warranty. Reference the TCNA Handbook and ANSI for installation guidance. Please visit bedrosians.com for current product information. We reserve the right to make product changes at any time without notice.

